

Fuse-link, low voltage, 100 A, AC 500 V, 120 kA, 22 x 58 mm, gL/gG, IEC

Part no. CYLINDRICAL FUSE 22 x 58 100A GG 500V AC
Catalog No. C22G100EL-Nummer 1664189
(Norway)

Powering Business Worldwide™

Delivery program

Product range		Fuse
Basic function		Fuse-link
Field of application		low voltage
Rated current	I	A
Rated voltage		AC 500 V
Size		22 x 58 mm
Utilization category		gL/gG
Breaking Capacity		kA
usable for size/applications		120
Standard/Approval		for industrial applications for general purpose use
Shape		IEC
Standards/Regulations		cylindrical
		IEC 60269-2

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])

Model		Ceramic fuse
Size		22x58 mm
Voltage type		AC
Rated current	A	100
Rated voltage	V	500
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	120
Power loss at rated current	W	9