



SENTRON, Switch disconnector 3LD, main switch, 3-pole, I_u: 16 A, Operating power / at AC-23 A at 400 V: 7.5 kW, front-mounted, rotary operating mechanism, black, 4-hole mounting of the handle

Model	
product brand name	SENTRON
product designation	Switch disconnector
design of the product	Main switch
display version for switch position indicator manual operation	1 ON - 0 OFF
type of switch	front mounted
design of the actuating element	Short rotary knob
color of the actuating element	black
design of handle	rotary operating mechanism, black
type of the driving mechanism motor drive	No
General technical data	
number of poles	3
size of switch disconnector	1
mechanical service life (operating cycles) typical	100 000
electrical endurance (operating cycles)	
• at AC-23 A at 690 V	6 000
operating frequency maximum	50 1/h
degree of pollution	3
Voltage	
insulation voltage rated value	690 V
surge voltage resistance rated value	6 kV
operating voltage	
• at AC rated value	690 V
operating frequency rated value	
• minimum	50 Hz
• maximum	60 Hz
Protection class	
protection class IP	IP65
degree of protection NEMA rating	1, 3R, 4X, 12
protection class IP on the front	IP65
Dissipation	
power loss [W] for rated value of the current at AC in hot operating state per pole	0.5 W
Main circuit	
operational current	
• at AC-21 at 690 V rated value	16 A
• at AC-21 A at 240 V rated value	16 A
• at AC-21 A at 400 V rated value	16 A
• at AC-21 A at 440 V rated value	16 A
• at AC-23 A at 400 V rated value	16 A

operating power		
• at AC-23 A at 240 V rated value		4 kW
• at AC-23 A at 400 V rated value		8 kW
• at AC-23 A at 440 V rated value		7.5 kW
• at AC-23 A at 690 V rated value		8 kW
• at AC-3 at 240 V rated value		3 kW
• at AC-3 at 400 V rated value		6 kW
• at AC-3 at 690 V rated value		5.5 kW
Auxiliary circuit		
number of CO contacts for auxiliary contacts	0	
number of NC contacts for auxiliary contacts	0	
number of NO contacts for auxiliary contacts	0	
operating voltage of auxiliary contacts at AC maximum	500 V	
continuous current of the auxiliary contact rated value	10 A	
Suitability		
suitability for use		
• main switch	Yes	
• switch disconnector	Yes	
• EMERGENCY OFF switch	No	
• safety switch	Yes	
• maintenance/repair switch	Yes	
Product details		
product feature can be locked into OFF position	Yes	
accessories		
product extension optional		
• motor drive	No	
• voltage trigger	No	
number of connectable NC contacts for auxiliary contacts attachable maximum	3	
number of connectable NO contacts for auxiliary contacts attachable maximum	3	
number of connectable CO contacts for auxiliary contacts attachable maximum	0	
number of bracket locks maximum	3	
hasp thickness of the bracket locks	4 ... 8 mm	
Short circuit		
conditional short-circuit current with line-side fuse protection		
• at 690 V by gG fuse rated value	50 kA	
let-through current with closed switch		
• at 240 V for combination switch + gG fuse maximum	3 kA	
• at 440 V for combination switch + gG fuse maximum	3 kA	
• at 690 V for combination switch + gG fuse maximum permissible	3 kA	
I _{2t} value with closed switch		
• at 240 V for combination switch + gG fuse maximum	2.5 kA2.s	
• at 440 V for combination switch + gG fuse maximum	2.5 kA2.s	
• at 690 V for combination switch + gG fuse maximum	3 kA2.s	
design of the fuse link		
• for short-circuit protection of the main circuit required	fuse gL/gG: 20 A	
• for short-circuit protection of the auxiliary switch required	fuse gL/gG: 10 A	
operational current of upstream fuse rated value	20 A	
according UL		
operational current at AC according to UL 508/UL 60947-4-1 rated value	16 A	
operating voltage at AC at 50/60 Hz according to UL 508/UL 60947-4-1 rated value	600 V	
active power [hp] at AC at 480 V according to UL 508/UL 60947-4-1 rated value	7.5	
active power [hp] at AC at 600 V according to UL 508/UL 60947-4-1 rated value	10	
short-time withstand current (SCCR) at 600 V according to UL 508/UL 60947-4-1	5 kA	
continuous current of upstream fuse according to UL rated value	50 A	

type of fuse according to UL	RK5
Connections	
AWG number as coded connectable conductor cross section solid maximum	
•	10
•	18
type of connectable conductor cross-sections for copper conductor	
• solid	1x (1...6mm ²)
• finely stranded with core end processing	1x (1...4mm ²)
• stranded	1x (1.6mm ²)
type of connectable conductor cross-sections for auxiliary contacts	
• solid	lateral auxiliary switch 2x (0,75 ... 2,5mm ²), 1x 4mm ² ; front auxiliary switch 1x (0,75 ... 2,5mm ²)
• finely stranded with core end processing	lateral auxiliary switch 2x (0,75 ... 1,5mm ²), 1x 2,5mm ² ; front auxiliary switch 1x 2,5mm ²
• stranded	lateral auxiliary switch 2x (0,75 ... 2,5mm ²), 1x 4mm ² ; front auxiliary switch 1x (0,75 ... 2,5mm ²)
type of electrical connection	
• for main current circuit	box terminal
• for auxiliary contacts	connection terminals

Mechanical Design	
height	84 mm
width	67 mm
depth	92.5 mm
type of device	fixed mounting
fastening method	Built-in unit fixed-mounted version
fastening method	
• 4-hole front mounting	Yes
• front mounting with central attachment	No
• rail mounting	No
net weight	188 g

Environmental conditions	
ambient temperature during operation	
• minimum	-25 °C
• maximum	55 °C
ambient temperature during storage	
• minimum	-25 °C
• maximum	55 °C

Approvals Certificates	
General Product Approval	



[Confirmation](#)



CCC



UL



VDE

General Product Approval	Marine / Shipping	other
--------------------------	-------------------	-------

[Miscellaneous](#)



[Miscellaneous](#)

[Confirmation](#)

Environment

[Environmental Con-](#)
[firmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD2003-0TK51>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3LD2003-0TK51>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD2003-0TK51

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





