SIEMENS

Data sheet

5TT4205-0



switching relay with 1 NO and 1 NC contact, contact for 230V AC 16A control 230V AC

Model	
product brand name	SENTRON
product designation	Switching relays
design of the product	with 1 NC and 1 NO
design of the switching function	1 NO + 1 NC
General technical data	
operating range factor of control voltage_1	0.8
electrical endurance (operating cycles)	50 000
galvanic isolation between magnet coil and contact	Yes
switching voltage of the contacts at AC minimum	10 V
switching current at AC per contact minimum	100 mA
power loss [V·A] of magnet coil with pulse rated value	3 VA
Voltage	
type of voltage of the operating voltage	AC
control voltage at AC rated value maximum	230 V
surge voltage resistance rated value	4 kV
Supply voltage	
operating voltage	
• minimum	400 V
• maximum	400 V
at AC rated value maximum	400 V
type of voltage of the supply voltage	AC
Protection class	
protection class IP	IP20, with connected conductors
Breaking Capacity	
switching capacity apparent power	
 for uncompensated fluorescent lamp load 	400 VA
switching capacity current at cos phi 0.6	16 A
switching capacity active power with incandescent lamp load	1 200 W
Dissipation	
power loss [W]	
 for rated value of the current at AC in hot operating state per pole 	1 W
 at 16 A per contact rated value 	1 W
 of magnet coil with pulse rated value 	2.4 W
Main circuit	
operating frequency rated value	50 Hz
operational current	
rated value	16 A
 at cos phi 0.6 1 rated value 	16 A

Control current	
type of voltage	
 of control voltage_1 	AC
control voltage	
 _1 initial value 	230 V
 _1 full-scale value 	230 V
control voltage frequency	
 _1 initial value 	50 Hz
 _1 full-scale value 	50 Hz
operating range factor of control voltage_2	1.1
number of NC contacts	1
number of NO contacts	1
number of CO contacts	0
Product function	
product function direct operation	Yes
Inputs Outputs	
relay design	partially electronic
Number	
number of terminals with cross-head screw	1
Connections	
connectable conductor cross-section for flexible conductor with core end processing	
• minimum	1 mm ²
• maximum	6 mm ²
connectable conductor cross-section for rigid conductor	
• minimum	1 mm ²
• maximum	6 mm ²
Mechanical Design	
width of opening of the contacts	1.2 mm
installation depth	90 mm
number of modular width units	1
fastening method	DIN rail
mounting position	any
required spacing for live parts	6 mm
Environmental conditions	
ambient temperature during operation	
	-10 °C
• maximum	40 °C
Annrovals Certificates	
General Product Approval	
UK (C	
EG-Konf.	CCC VDE
General Product Approval Test Certificates other	Environment
Miscellaneous Confirmation	n <u>Miscellaneous</u> <u>Environmental Con-</u> <u>Environmental Con-</u>
FHI	<u>tirmations</u> <u>tirmations</u>
LIIL	
Further information	
Information on the packaging	

https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT4205-0 Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/5TT4205-0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4205-0

CAx-Online-Generator http://www.siemens.com/cax

Tender specifications

http://www.siemens.com/specifications



last modified:

10/15/2021 🖸