

PRODUCT-DETAILS

8187.9

8187.9 French/Earth-pin socket outlet for plain covers



General Information

Extended Product Type	8187.9
Product ID	2CLA818790A1001
EAN	8427238161990
Catalog Description	8187.9 French/Earth-pin socket outlet for plain covers
Long Description	Rated voltage: 250 Vac Rated current: 16A Type E: 2P + E Shuttered for child safety Screwless terminals Included: fixing claws Cover plate code: 8587.9

Technical

Rated Voltage (U_r)	250 V
Rated Current (I_n)	16 A
Frequency (f)	50...60 Hz
Number of Phases	2
Number of Gangs	1
Connection Type	Plug Clamp
Mounting Type	Flush Mounted
Socket Outlet Type	Power Socket Outlets - French acc. to NF C 61-314
Type of Fastening	Screw
Label Space Provided	No
Legend	Without imprint

Model Number	French norm NF
Number of Batteries	0

Environmental

Ambient Air Temperature	Operation -5 ... +35 °C Storage -5 ... +50 °C
Degree of Protection	IP20
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Dimensions

Product Net Width	0.145 m
Product Net Height	0.074 m
Product Net Depth / Length	0.216 m
Product Net Weight	0.066 kg

Container Information

Package Level 1 Units	box 10 piece
Package Level 1 Width	0.145 m
Package Level 1 Height	0.074 m
Package Level 1 Depth / Length	0.216 m
Package Level 1 Gross Weight	0.66 kg
Package Level 1 EAN	8427238161990

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85366990
Country of Origin	Spain (ES)

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK1074920617
Instructions and Manuals	No document needed
REACH Declaration	9AKK108467A7464
RoHS Information	2CLC818790A1001

Popular Downloads

Data Sheet, Technical Information	9AKK107046A0356
Instructions and Manuals	No document needed

Classifications

ETIM 7	EC000125 - Socket outlet
ETIM 8	EC000125 - Socket outlet

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85366990

Categories

Low Voltage Products and Systems → Switch Assortments → Inserts → Sockets

