



Terminal plate, 35-120mm², 81mm

Part no. BBA-TP3/120
Catalog No. 107184


EL-Nummer 2465022
(Norway)

Delivery program

Product range			60 mm system
Basic function			Connections
Subrange			Clamp plate
Material			Silicon free, chlorine free
Self-extinguishing			to UL 94
Track resistance			CTI 200
Temperature resistant			to 120°C
Description			The terminal can be removed for the connection of uncut conductors Looping is possible
Terminal area W x H		mm	15 x 15
Width		mm	81
Pole			3
Rated operational current	I _e	A	440
conductor			35 - 120 mm ² AWG 2 - MCM 250.   # 10 x 16 x 0.8
Cu factor		kg	0,05
For use with			12 x 5/10 15 x 5/10 20 x 5/10 25 x 5/10 30 x 5/10
For use with			Double T profile

Notes

○ round conductor, solid

 Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

 Sector conductor, solid

Sector conductor, stranded

CU band

■ CU busbar

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)

Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ec1@ss10.0.1-27-14-11-46 [BAA025013])

Busbar thickness		mm	5 - 10
Busbar width		mm	12 - 30
Suitable for			Flat rail
Width clamp		mm	81
Max. conductor cross section		mm ²	120
Max. rated operation current I _e		A	440
Suitable for round conductor connection			Yes
Suitable for sector conductor connection			Yes
Suitable for strip conductor connection			Yes

