

Clamp terminal for copper band, for 20x5-30x10

Part no. AKS-CU-BAND
Catalog No. 107197

EL-Nummer 2465035
(Norway)

Delivery program

Product range			60 mm system 185 mm system
Basic function			Connections
Subrange			Clamp terminals
Description			Termination to busbars without drilling A contact block is used to connect the conductor to the busbar
Terminal area W x H		mm	32 x 25
Width		mm	41
Rated operational current	I _e	A	800
conductor			# 3 x 20 x 1 mm up to 2x (10 x 32 x 1 mm) ■ 32 x 25 mm
Cu factor		kg	0,00
For use with			20 x 5/10 25 x 5/10 30 x 5/10
For use with			Double T profile
Notes			
○ round conductor, solid			
● Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
💡 Section conductor, solid			
Sector conductor, stranded			
# CU band			
■ CU busbar			

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)		
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])		
Busbar thickness	mm	5 - 10
Busbar width	mm	20 - 30
Suitable for		Flat rail
Width clamp	mm	41
Max. conductor cross section	mm ²	800
Max. rated operation current I _e	A	800
Suitable for round conductor connection		Yes
Suitable for sector conductor connection		Yes
Suitable for strip conductor connection		Yes