








Clamp terminal 95-185mm², for 20x5-30x10

Part no. AKS185
Catalog No. 107195

EL-Nummer (Norway) 2465033

Delivery program

| | | | |
|--|----------------|----|---|
| Product range | | | 60 mm system 185 mm system |
| Basic function | | | Connections |
| Subrange | | | Clamp terminals |
| Description | | | Termination to busbars without drilling A cable block is used to connect the conductor to the busbar |
| Width | | mm | 38 |
| Rated operational current | I _e | A | 500 |
| conductor | | | 95 - 185 mm ² AWG3/0 - MCM350. directly terminated:    |
| Cu factor | | kg | 0,00 |
| For use with | | | 20 x 5/10 25 x 5/10 30 x 5/10 |
| For use with | | | Double T profile |
| Notes  round conductor, solid  Flexible, round conductor with correctly crimped ferrule Round conductor, stranded  Sector conductor, solid Sector conductor, stranded # CU band  CU busbar | | | |

Technical data ETIM 8.0

| | | | |
|--|--|-----------------|-----------|
| Low-voltage industrial components (EG000017) / Busbar terminal (EC000001) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013]) | | | |
| Busbar thickness | | mm | 5 - 10 |
| Busbar width | | mm | 20 - 30 |
| Suitable for | | | Flat rail |
| Width clamp | | mm | 38 |
| Max. conductor cross section | | mm ² | 185 |
| Max. rated operation current I _e | | A | 500 |
| Suitable for round conductor connection | | | Yes |
| Suitable for sector conductor connection | | | Yes |
| Suitable for strip conductor connection | | | Yes |