

Busbar adapter, 45 mm, 16 A, DIN rail: 2



Part no.	BBA0C-16
Catalog No.	101455
Alternate Catalog No.	BBA0C-16
EL-Nummer (Norway)	2465050

Delivery program

				This item can only be ordered until December 31, 2023 with a maximum delivery date of May 31, 2024.
Accessories		Busbar adapters		
		Approved to UL 508 For fitting to flat Cu-busbars with 60 mm between busbar centres, suitable for 5 mm and 10 mm busbar thickness Rated operational current 16 A For starter with springloaded terminals		
For use with		Busbar adapters PKZ0		
Rated operational voltage		U _e	V	690
Rated operational current		I _e	A	16
Terminal capacity		AWG 14 (2.5 mm ²)		
Adapter width		mm		45
Adapter length		mm		200
DIN rail		Quantity		2
Adapter width		mm		45
For use with		PKZM0-C + DILMC7 PKZM0-C + DILMC9 PKZM0-C + DILMC12		

Notes According to UL 508: I_e = 12 A

Design verification as per IEC/EN 61439

Technical data for design verification				
Rated operational current for specified heat dissipation	I _n	A	16	
Heat dissipation per pole, current-dependent	P _{vid}	W	0	
Equipment heat dissipation, current-dependent	P _{vid}	W	0.8	
Static heat dissipation, non-current-dependent	P _{vs}	W	0	
Heat dissipation capacity	P _{diss}	W	0	
Operating ambient temperature min.		°C	-25	
Operating ambient temperature max.		°C	55	
IEC/EN 61439 design verification				
10.2 Strength of materials and parts				
10.2.2 Corrosion resistance			Meets the product standard's requirements.	
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.	
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.	
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.	
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.	
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.	
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.	
10.2.7 Inscriptions			Meets the product standard's requirements.	
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.	
10.4 Clearances and creepage distances			Meets the product standard's requirements.	
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.	
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.	
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.	
10.8 Connections for external conductors			Is the panel builder's responsibility.	

10.9 Insulation properties		
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Busbar adapter (EC001531)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar adapter (low-voltage switching technology) (ecl@ss10.0.1-27-37-03-04 [ACN951011])		
Mounting rail armament		2 mounting rails
Type of electric connection		Round conductor
Rated current In	A	16
Min. busbar thickness	mm	5
Max. busbar thickness	mm	10
Width of the adapter	mm	45
Rail width	mm	35
Busbar distance	mm	60