

**Floor-standing distribution board with locking rotary lever, IP55,
HxWxD=1760x800x320mm**



Part no. BPM-F-800/17-P
Catalog No. 111051

**EL-Nummer
(Norway)** 2459503

Delivery program

Mounting type			Floor standing distribution board
Material			Sheet steel
Door interlock			Rotary lever
Installation site			Moisture-proof
Degree of Protection			IP55
Surface finish			With powder coating
Width		mm	800
Depth		mm	320
Height		mm	1760
Colour			light gray (RAL 7035)

Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure, free-standing	P _V	W	198
Starting enclosure, free-standing	P _V	W	193
Middle enclosure, free-standing	P _V	W	195
Individual enclosure for wall mounting	P _V	W	183
Starting enclosure for wall mounting	P _V	W	167
Middle enclosure for wall mounting	P _V	W	154
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure, free-standing	P _V	W	398
Starting enclosure, free-standing	P _V	W	388
Middle enclosure, free-standing	P _V	W	391
Individual enclosure for wall mounting	P _V	W	367
Starting enclosure for wall mounting	P _V	W	335
Middle enclosure for wall mounting	P _V	W	310
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Not relevant to indoor installations.
10.2.5 Lifting			Met; assembled and secured as per the latest applicable instruction leaflet.
10.2.6 Mechanical impact			IK10
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			IP55
10.4 Clearances and creepage distances			Is the panel builder's responsibility.
10.5 Protection against electric shock			< 0.1 Ω; meets the product standard's requirements.
10.6 Incorporation of switching devices and components			Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.

10.9 Insulation properties			
10.9.2 Power-frequency electric strength			$U_i = 440 \text{ V AC}$
10.9.3 Impulse withstand voltage			4 kV
10.9.4 Testing of enclosures made of insulating material			Does not apply to metal enclosures.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.
10.13 Mechanical function			Meets the product standard's requirements.

Technical data ETIM 8.0

Cabinet enclosures (EG000011) / Enclosure/cabinet (empty) (EC000261)

Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet (ecl@ss10.0.1-27-18-01-01 (AGZ056016))

Width	mm	830
Height	mm	1790
Depth	mm	350
Material		Steel
Material quality		Other
Surface finishing		Powder coating
Colour		Grey
RAL-number		7035
Detached		Yes
Floor standing wall model		No
Suitable for wall mounting		No
Corner model		No
Intermediate mounting		No
Connectable		No
With mounting plate		No
Mounting plate depth-adjustable		No
Suitable for wall built-in		No
Pole fastening		No
Number of doors		1
Number of locks		0
Suitable for metrical mounting		Yes
Suitable for outdoor set-up		No
Pitched roof		No
EMC-version		Yes
With glazed door		No
With ventilation door		No
With backside door		No
Impact strength		IK10
Degree of protection (IP)		IP55
Degree of protection (NEMA)		Other
Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890	W	0
Max. permissible load of the enclosure according to IEC 62208	N	0
Max. permissible load of the door(s) according to IEC 62208	N	0
Max. permissible load of the mounting plate according to IEC 62208	N	0