

Replacement coil, RA 250: 110 - 250 V 40-60 Hz/110 - 250 V DC, AC and DC operation, For use with: DILM250, DILM300A



**Part no.** DILM250-XSP/E(RA250)  
**Catalog No.** 208252  
**Alternate Catalog No.** XTCERENCOILLA  
**EL-Nummer (Norway)** 4134023

## Delivery program

Actuating voltage		RA 250: 110 - 250 V 40-60 Hz/110 - 350 V DC
Voltage AC/DC		AC and DC operation
For use with		DILM185 DILM225 DILM250 DILM300A
Instructions		The following items are predecessor models and are no longer available: DILM185(-S), DILM225(-S), DILM300(-S)

## Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	°C	-40	
Operating ambient temperature max.	°C	60	

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])			
Rated control supply voltage Us at AC 50Hz	V	110 - 250	
Rated control supply voltage Us at AC 60Hz	V	110 - 250	
Rated control supply voltage Us at DC	V	110 - 250	
Voltage type for actuating		AC/DC	