

Replacement coil, Tool-less plug connection, RAC 240: 190 - 240 V 50/60 Hz, AC, For use with: DILM115, DILM150, DILM170, DILMP125 - DILMP200



Part no. DILM150-XSP(RAC240)
Catalog No. 230112
Alternate Catalog No. XTCERENCOILGB
EL-Nummer (Norway) 4130505

Delivery program

Actuating voltage		RAC 240: 190 - 240 V 50/60 Hz
Voltage AC/DC		AC
For use with		DILM115 DILM150 DILM170 DILMP125 - DILMP200
For use with		DILM115 - DILM170 (incl. electronic module)

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	°C	-25	
Operating ambient temperature max.	°C	60	

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])			
Rated control supply voltage Us at AC 50HZ	V	190 - 240	
Rated control supply voltage Us at AC 60HZ	V	190 - 240	
Rated control supply voltage Us at DC	V	0 - 0	
Voltage type for actuating		AC	