

Replacement coil, Tool-less plug connection, 230 V 50 Hz, 240 V 60 Hz, AC,
For use with: DILM40, DILM50, DILM65, DILM72, DILMP63, DILMP80



Part no. **DILM65-XSP(230V50HZ,240V60HZ)**
 Catalog No. **281171**
 Alternate Catalog No. **XTCERENCOILDF**
 EL-Nummer (Norway) **4130503**

Delivery program

Actuating voltage		230 V 50 Hz, 240 V 60 Hz
Voltage AC/DC		AC
For use with		DILM40 DILM50 DILM65 DILM72 DILMP63 DILMP80
For use with		DILM40 - DILM72

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	°C	-25	
Operating ambient temperature max.	°C	60	

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])			
Rated control supply voltage Us at AC 50Hz	V	230 - 230	
Rated control supply voltage Us at AC 60Hz	V	240 - 240	
Rated control supply voltage Us at DC	V	0 - 0	
Voltage type for actuating		AC	