



Figure similar

Digital monitoring relay Current monitoring, 22.5 mm from 0.05-10 A AC/DC  
 Overshoot and undershoot 24 to 240 V AC/DC 50 to 60 Hz DC and AC ON  
 delay and noise pulses delay 0.1 to 20 s Hysteresis 0.01 to 5 A 1 change-over contact with or without fault buffer spring-type connection system

product brand name	SIRIUS
product designation	Current monitoring relay with digital setting
product type designation	3UG4
<b>General technical data</b>	
product function	Current monitoring relay
design of the display	LCD
insulation voltage for overvoltage category III according to IEC 60664	690 V
• with degree of pollution 3 rated value	3
degree of pollution	4 kV
surge voltage resistance rated value	300 V
maximum permissible voltage for safe isolation	300 V
• between auxiliary and auxiliary circuit	IP20
• between control and auxiliary circuit	sinusoidal half-wave 15g / 11 ms
protection class IP	1 ... 6 Hz: 15 mm, 6 ... 500 Hz: 2g
shock resistance according to IEC 60068-2-27	10 000 000
vibration resistance according to IEC 60068-2-6	100 000
mechanical service life (operating cycles) typical	5 A
electrical endurance (operating cycles) at AC-15 at 230 V typical	K
thermal current of the switching element with contacts maximum	1 %
reference code according to IEC 81346-2	05/01/2012
relative repeat accuracy	
Substance Prohibitance (Date)	
<b>Product Function</b>	
product function	
• overcurrent detection 1 phase	Yes
• overcurrent detection 3 phase	No
• underright detection 1 phase	Yes
• underright detection 3 phases	No
• overcurrent detection DC	Yes
• underright detection DC	Yes
• current window recognition DC	Yes
• voltage window recognition 1 phase	No
• voltage window recognition 3 phase	No
• adjustable open/closed-circuit current principle	Yes
• external reset	Yes
• auto-RESET	Yes
<b>Supply voltage</b>	
type of voltage of the supply voltage	AC/DC

<b>supply voltage 1 at AC</b>	
• at 50 Hz	20.4 ... 264 V
• at 60 Hz	20.4 ... 264 V
<b>supply voltage 1 at DC</b>	20.4 ... 264 V
<b>Measuring circuit</b>	
<b>type of current for monitoring</b>	AC/DC
<b>measurable current</b>	0.05 ... 15 A
<b>measurable line frequency</b>	40 ... 500 Hz
<b>adjustable current response value current</b>	
• 1	0.05 ... 10 A
• 2	0.05 ... 10 A
<b>adjustable response delay time</b>	
• when starting	0.1 ... 20 s
• with lower or upper limit violation	0.1 ... 20 s
<b>adjustable switching hysteresis for measured current value</b>	10 ... 5 000 mA
<b>buffering time in the event of power failure minimum</b>	10 ms
<b>accuracy of digital display</b>	+/-1 digit
<b>relative temperature-related measurement deviation</b>	5 %
<b>internal resistance of the measuring circuit</b>	5 mΩ
<b>Precision</b>	
<b>relative metering precision</b>	5 %
<b>temperature drift per °C</b>	0.1 %/°C
<b>Auxiliary circuit</b>	
number of NC contacts delayed switching	0
number of NO contacts delayed switching	0
number of CO contacts delayed switching	1
<b>operating frequency with 3RT2 contactor maximum</b>	5 000 1/h
<b>Main circuit</b>	
<b>number of poles for main current circuit</b>	1
operating voltage rated value	24 ... 240 V
<b>ampacity of the output relay at AC-15</b>	
• at 250 V at 50/60 Hz	3 A
• at 400 V at 50/60 Hz	3 A
<b>ampacity of the output relay at DC-13</b>	
• at 24 V	1 A
• at 125 V	0.2 A
• at 250 V	0.1 A
<b>operational current at 17 V minimum</b>	0.005 A
<b>continuous current of the DIAZED fuse link of the output relay</b>	4 A
<b>Electromagnetic compatibility</b>	
<b>conducted interference</b>	
• due to burst according to IEC 61000-4-4	2 kV
• due to conductor-earth surge according to IEC 61000-4-5	2 kV
• due to conductor-conductor surge according to IEC 61000-4-5	1 kV
<b>field-based interference according to IEC 61000-4-3</b>	10 V/m
<b>electrostatic discharge according to IEC 61000-4-2</b>	6 kV contact discharge / 8 kV air discharge
<b>Galvanic isolation</b>	
<b>design of the electrical isolation</b>	Protective separation
<b>galvanic isolation</b>	
• between input and output	Yes
• between the outputs	Yes
• between the voltage supply and other circuits	Yes
<b>Connections/ Terminals</b>	
<b>product component removable terminal for main circuit</b>	Yes
<b>product component removable terminal for auxiliary and control circuit</b>	Yes
<b>type of electrical connection</b>	
• for main current circuit	spring-loaded terminals

• for auxiliary and control circuit	spring-loaded terminals
<b>type of connectable conductor cross-sections</b>	
• solid	2x (0.25 ... 1.5 mm <sup>2</sup> )
• finely stranded with core end processing	2 x (0.25 ... 1.5 mm <sup>2</sup> )
• finely stranded without core end processing	2x (0.25 ... 1.5 mm <sup>2</sup> )
• at AWG cables solid	2x (24 ... 16)
• at AWG cables stranded	2x (24 ... 16)
<b>connectable conductor cross-section</b>	
• solid	0.25 ... 1.5 mm <sup>2</sup>
• finely stranded with core end processing	0.25 ... 1.5 mm <sup>2</sup>
• finely stranded without core end processing	0.25 ... 1.5 mm <sup>2</sup>
<b>AWG number as coded connectable conductor cross section</b>	
• solid	24 ... 16
• stranded	24 ... 16

<b>Installation/ mounting/ dimensions</b>	
<b>mounting position</b>	any
<b>fastening method</b>	snap-on mounting
<b>height</b>	94 mm
<b>width</b>	22.5 mm
<b>depth</b>	91 mm
<b>required spacing</b>	
• with side-by-side mounting	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm
• for grounded parts	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— at the side	0 mm
— downwards	0 mm
• for live parts	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm

<b>Ambient conditions</b>	
installation altitude at height above sea level maximum	2 000 m
<b>ambient temperature</b>	
• during operation	-25 ... +60 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C

<b>Certificates/ approvals</b>		
<b>General Product Approval</b>	<b>EMC</b>	<b>Declaration of Conformity</b>



[Confirmation](#)



<b>Declaration of Conformity</b>	<b>Test Certificates</b>	<b>Marine / Shipping</b>	<b>other</b>
----------------------------------	--------------------------	--------------------------	--------------



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



[Confirmation](#)

**Further information**

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UG4622-2AW30>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UG4622-2AW30>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3UG4622-2AW30>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3UG4622-2AW30&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UG4622-2AW30&lang=en)

**Characteristic: Derating**

<https://support.industry.siemens.com/cs/ww/en/ps/3UG4622-2AW30/manual>

