

PRODUCT-DETAILS

DDA204 A-63/0.03 110V DDA204 A-63/0.03 110V Residual Current Device Block



| General Information | |
|-----------------------|---|
| Extended Product Type | DDA204 A-63/0.03 110V |
| Product ID | 2CSB204199R1630 |
| EAN | 8012542812104 |
| Catalog Description | DDA204 A-63/0.03 110V Residual Current Device Block |
| Long Description | The RCD block DDA200 series is suitable for assembly with MCBs S200 series and S300P. It assures protection against the effects of sinusoidal alternating and direct pulsating earth fault currents, protection, against indirects contacts and additional protection against direct (with sensitivity = 30 mA) contacts. Operating voltage of circuit test: 110V. Applications: naval, industrial. |

| Technical | |
|---|------------------|
| Standards | IEC 61009 Ann. G |
| Type of Residual Current | A type |
| Rated Voltage (U _r) | 230400 V |
| Rated Operational Voltage | 230/400 V |
| Rated Insulation Voltage (U _i) | 500 V |
| Test Voltage (Ut) | 110 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 4 kV |
| Rated Current (I _n) | 63 A |
| Rated Residual Current | 30 mA |
| Leakage Current Type | A |

DDA204 A-63/0.03 110V 2

| Rated Frequency (f) | 50/60 Hz |
|--|---------------------------------------|
| Power Loss | 7.6 W |
| Power Supply Connection | Arbitrary |
| Electrical Endurance | 10000 cycle |
| Number of Poles | 4 |
| Operating Characteristic | Instantaneous |
| Options Provided | Suitable for 110V applications |
| Connecting Capacity | Rigid 25 25 mm² |
| | Flexible 25 25 mm ² |
| Environmental | |
| Ambient Temperature | -2555 °C |
| Ambient Air Temperature | Operation -2555 °C |
| Degree of Protection | IP2X |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 0.1 mm or 1 g - 20 cycles at 51505 Hz |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g 2 shocks 13 ms |
| RoHS Status | Following EU Directive 2011/65/EU |
| Environmental Information | Refer to RoHS |
| Technical UL/CSA | |
| Short-Circuit Current Rating (SCCR) | 0.03 0.03 A |
| | |
| Dimensions | |
| Product Net Width | 140 mm |
| Product Net Height | 93 mm |
| Product Net Depth / Length | 76 mm |
| Product Net Weight | 0.311 kg |
| Ocatain an Information | |
| Container Information | |
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 146 mm |
| Package Level 1 Height | 80 mm |
| Package Level 1 Depth / Length | 104 mm |
| Package Level 1 Gross Weight | 0.368 kg |
| Package Level 1 EAN | 8012542812111 |
| Ordering | |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85363030 |
| Country of Origin | Italy (IT) |
| | |

DDA204 A-63/0.03 110V 3

| Declaration of Conformity - CE | 9AKK106713A5614 |
|--------------------------------|-----------------|
| Environmental Information | Refer to RoHS |
| Instructions and Manuals | 9AKK108467A7091 |
| RoHS Information | 9AKK106713A5614 |

| Popular Downloads | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107991A8329 |
| Instructions and Manuals | 9AKK108467A7091 |

| Classifications | | |
|----------------------------|--|--|
| ETIM 7 | EC002297 - Residual current circuit breaker (RCCB) module | |
| ETIM 8 | EC002297 - Residual current circuit breaker (RCCB) module | |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) | |
| WEEE B2C / B2B | Business To Consumer | |
| CN8 | 85363030 | |
| eClass | V11.0 : 27142210 | |
| Object Classification Code | F | |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCD Blocks

