

Lamp load contactor, 230 V 50 Hz, 240 V 60 Hz, 220 V 230 V: 18 A,  
Contactors for lighting systems



Part no. DILL18(230V50HZ,240V60HZ)  
Catalog No. 104405  
Alternate Catalog XTCT018C00F  
No.  
EL-Nummer 4134239  
(Norway)

Delivery program

Product range			DILL Lighting contactors																								
Application			Contactors for lighting systems																								
Utilization category			AC-1: Non-inductive or slightly inductive loads, resistance furnaces																								
Rated operational current																											
AC-5a																											
220 V 230 V	I <sub>e</sub>	A	18																								
380 V 400 V	I <sub>e</sub>	A	18																								
AC-5b																											
220 V 230 V	I <sub>e</sub>	A	21																								
380 V 400 V	I <sub>e</sub>	A	21																								
AC-1																											
Conventional free air thermal current, 3 pole, 50 - 60 Hz																											
Open																											
at 40 °C	I <sub>th</sub> = I <sub>e</sub>	A	40																								
Actuating voltage			230 V 50 Hz, 240 V 60 Hz																								
Note			<div>Switchgear for lighting systems</div> <table><tr><td>DIL</td><td>L12</td><td>L18</td><td>L20</td><td>M7</td><td>M9</td><td>M12</td><td>M17</td><td>M25</td><td>M32</td><td>M40</td><td>M50</td></tr><tr><td>Permissible completion capacitance</td><td>70</td><td>470</td><td>470</td><td>47</td><td>80</td><td>100</td><td>220</td><td>330</td><td>470</td><td>470</td><td>500</td></tr></table> <div>Filament (A)14 21 27 6 7.5 10 14 21 27 33 42 lamp Mercury (A)12 16 23 5 6.5 8.5 12 16 23 30 38 blended lamps Fluorescent (A)20 26 35 9 10 15 20 26 35 41 45 lamps, conventional - reactor - starter - connection Fluorescent (A)20 26 35 5.5 8 13 15 22.5 29 36 47 lamps, conventional - reactor - starter - connection Fluorescent (A)12 18 20 5 6.5 8.5 12 17.5 22.5 28 35 lamps, duo circuit (series compensated) electronic (A)12 18 20 3.5 6 10 12 17.5 20 25 30 upstream devices and LED lamps High-le (A)12 18 20 3.5 6 10 12 17.5 20 25 30 pressure mercury- arc lamps</div>	DIL	L12	L18	L20	M7	M9	M12	M17	M25	M32	M40	M50	Permissible completion capacitance	70	470	470	47	80	100	220	330	470	470	500
DIL	L12	L18	L20	M7	M9	M12	M17	M25	M32	M40	M50																
Permissible completion capacitance	70	470	470	47	80	100	220	330	470	470	500																

			Switchgear for lighting systems													
			Metale [A]	12	18	20	3.5	6	10	12	17.5	20	25	30		
			halide lamps													
			Low-le [A]	7.5	10	12	3	4	6	7.5	10	12	15	22		
			pressure sodium lamps													
			DIL M65 M80 M95 M115M150M185M225M250M300M400M500A													
			Permissible compensation capacitance	500	550	620	830	970	2055	2300	2600	3000	3250	3500		
			Filament lamp													
			Mercury-blended lamps	45	65	67	80	110	123	150	167	200	266	332		
			Fluorescent lamps, conventional - reactor - starter - connection	55	67	79	95	125	153	187	208	349	332	415		
			Fluorescent lamps, conventional - reactor - starter - connection													
			Fluorescent lamps, conventional - reactor - starter - connection	55	71	95	100	138	186	213	236	270	338	473		
			Fluorescent lamps, duo circuit (series compensated) electronic upstream devices and LED lamps													
			High-le [A]	36	55	60	80	95	138	158	175	200	250	350		
			pressure mercury-arc lamps													
			Metale [A]	36	55	60	80	95	138	158	175	200	250	350		
			halide lamps													
			Low-le [A]	25	35	40	50	70	100	11	123	140	175	245		
			pressure sodium lamps													
			In compensated lamps, the sum of the capacitances must not exceed the contactors' max. permissible capacitor load (Cmax)!													
The values in the table are for each contact in the contactors.																

## Technical data

### General

Standards			IEC/EN 60947, VDE 0660, UL, CSA
Lifespan, mechanical			
AC operated	Operations	x 10 <sup>6</sup>	1
Operating frequency, mechanical			
AC operated	Operations/h		60
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Ambient temperature			
Open		°C	-25 - +60
Enclosed		°C	- 25 - 40
Storage		°C	- 40 - 80
Mechanical shock resistance (IEC/EN 60068-2-27)			
Half-sinusoidal shock, 10 ms			

Mechanical shock resistance		g	6.9
Degree of Protection			IP00
Altitude		m	Max. 2000
Weight			
AC operated		kg	0.42

### Main conducting paths

Rated impulse withstand voltage	$U_{imp}$	V AC	8000
Overvoltage category/pollution degree			III/3
Rated insulation voltage	$U_i$	V AC	690
Rated operational voltage	$U_e$	V AC	690
Making capacity		A	350
Breaking capacity	380 ... 400 V	A	250
Lifespan, electrical	Operations		10000
Short-circuit protection maximum fuse			
400 V	gG/gL 500 V	A	100

### AC

AC-1			
Rated operational current			
Conventional free air thermal current, 3 pole, 50 - 60 Hz			
Open			
at 40 °C	$I_{th} = I_e$	A	40
at 60 °C	$I_{th} = I_e$	A	35
AC-5a operation			
220 V 230 V	$I_e$	A	18
380 V 400 V	$I_e$	A	18
AC-5b operation			
220 V 230 V	$I_e$	A	21
380 V 400 V	$I_e$	A	21
380 V 400 V	$I_e$	A	21
Electric lamps			
Filament bulbs		A	21
Mercury blended lamps		A	16
Fluorescent lamp load			
Conventional reactor starter circuit		A	26
Duo circuit		A	26
Electronic upstream devices		A	18
High-pressure mercury vapour lamps		A	18
Metal-halide lamps		A	18
High-pressure sodium lamps		A	18
Low-pressure sodium lamps		A	10
Maximum permissible compensation capacitance		μF	470

### Current heat loss

Current heat loss at $I_e$ to AC-5b/400 V		W	3
Impedance per pole		mΩ	2.65

### Magnet systems

Voltage tolerance			
AC operated	Pick-up	x $U_c$	
Min. pick-up voltage, AC operated		x $U_c$	0.12
Pick-up voltage AC operated, max.		x $U_c$	1.5
Drop-out voltage AC operated	Drop-out	x $U_c$	
Drop-out voltage, AC-operated, min.		x $U_c$	0.3
Power consumption of the coil in a cold state and 1.0 x $U_S$			
Dual-voltage coil 50 Hz	Pick-up	VA	52
Dual-voltage coil 50 Hz	Sealing	VA	7.1
Dual-voltage coil 50 Hz	Sealing	W	2.1

Dual-voltage coil 60 Hz	Pick-up	VA	67
Dual-voltage coil 60 Hz	Sealing	VA	8.7
Dual-voltage coil 60 Hz	Sealing	W	2.1
Duty factor		% DF	100
Operating times			
Closing delay		ms	
Switching times of main contacts AC operated Closing delay, min.		ms	16
Switching times of main contacts AC operated Closing delay, max.		ms	22
Opening delay		ms	
Switching times of main contacts AC operated Opening delay, min.		ms	8
Switching times of main contacts AC operated Opening delay, max.		ms	14

Additional technical data

like the contactar	DIL		M25
--------------------	-----	--	-----

Rating data for approved types

Switching capacity			
General use		A	35
Short Circuit Current Rating		SCCR	
Basic Rating			
SCCR		kA	5
max. Fuse		A	125
max. CB		A	125
480 V High Fault			
SCCR (fuse)		kA	100
max. Fuse		A	100 Class J
SCCR (CB)		kA	22
max. CB		A	32
600 V High Fault			
SCCR (fuse)		kA	100
max. Fuse		A	100 Class J
SCCR (CB)		kA	22
max. CB		A	32
Special Purpose Ratings			
Incandescent Lamps (Tungsten)			
480V 60Hz 3phase, 277V 60Hz 1phase		A	35
600V 60Hz 3phase, 347V 60Hz 1phase		A	35

Electromagnetic compatibility (EMC)

Emitted interference			According to EN 60947-1
Interference immunity			According to EN 60947-1

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I <sub>n</sub>	A	21
Heat dissipation per pole, current-dependent	P <sub>vid</sub>	W	1
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	3
Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	2.1
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	60
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.

10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9 Insulation properties		
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])		
Rated control supply voltage Us at AC 50HZ	V	230 - 230
Rated control supply voltage Us at AC 60HZ	V	240 - 240
Rated control supply voltage Us at DC	V	0 - 0
Voltage type for actuating		AC
Rated operation current Ie at AC-1, 400 V	A	18
Rated operation current Ie at AC-3, 400 V	A	0
Rated operation power at AC-3, 400 V	kW	0
Rated operation current Ie at AC-4, 400 V	A	0
Rated operation power at AC-4, 400 V	kW	0
Rated operation power NEMA	kW	0
Modular version		No
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as normally closed contact		0
Type of electrical connection of main circuit		Screw connection
Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3