

Contactor, 3 pole, 380 V 400 V 18.5 kW, 42 V 50 Hz, 48 V 60 Hz, AC operation, Screw terminals



Part no. DILM40(42V50HZ,48V60HZ)
Catalog No. 277762
Alternate Catalog No. XTCE040D00W
EL-Nummer (Norway) 4130437

Delivery program

| | |
|----------------------|---|
| Product range | Contactors |
| Application | Contactors for Motors |
| Subrange | Contactors up to 170 A, 3 pole |
| Utilization category | AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-3/AC-3e: Normal AC induction motors: Starting, switching off while running AC-4: Normal AC induction motors: starting, plugging, reversing, inching |
| Notes | Also suitable for motors with efficiency class IE3. |
| Connection technique | Screw terminals |
| Number of poles | 3 pole |

Rated operational current

| | | | | |
|---|---|---|-----|--|
| AC-3 | | | | |
| Notes | At maximum permissible ambient temperature (open.) Also tested according to AC-3e. | | | |
| 380 V 400 V | I_e | A | 40 | |
| AC-1 | | | | |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz | | | | |
| Open | | | | |
| at 40 °C | $I_{th} = I_e$ | A | 60 | |
| enclosed | I_{th} | A | 45 | |
| Conventional free air thermal current, 1 pole | | | | |
| open | I_{th} | A | 125 | |
| enclosed | I_{th} | A | 112 | |

Max. rating for three-phase motors, 50 - 60 Hz

| | | | | |
|--|---|----|------|--|
| AC-3 | | | | |
| 220 V 230 V | P | kW | 12.5 | |
| 380 V 400 V | P | kW | 18.5 | |
| 660 V 690 V | P | kW | 23 | |
| AC-4 | | | | |
| 220 V 230 V | P | kW | 5 | |
| 380 V 400 V | P | kW | 9 | |
| 660 V 690 V | P | kW | 12 | |
| Can be combined with auxiliary contact | DILM150-XHI(V)... DILM1000-XHI(V)... | | | |
| Actuating voltage | 42 V 50 Hz, 48 V 60 Hz | | | |
| Voltage AC/DC | AC operation | | | |
| Connection to SmartWire-DT | no | | | |
| Instructions | Contacts to EN 50 012. | | | |
| Frame size | 3 | | | |

Technical data

| | | | |
|---------------------------------|------------|---------------------------------|----|
| General | | | |
| Standards | | IEC/EN 60947, VDE 0660, UL, CSA | |
| Lifespan, mechanical | | | |
| AC operated | Operations | $\times 10^6$ | 10 |
| Operating frequency, mechanical | | | |

| | | |
|---|-------------------------------------|--|
| AC operated | Operations/h | 5000 |
| Climatic proofing | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Ambient temperature | | |
| Open | °C | -25 - +60 |
| Enclosed | °C | -25 - 40 |
| Storage | °C | -40 - 80 |
| Mechanical shock resistance (IEC/EN 60068-2-27) | | |
| Half-sinusoidal shock, 10 ms | | |
| Main contacts | | |
| N/O contact | g | 10 |
| Auxiliary contacts | | |
| N/O contact | g | 7 |
| N/C contact | g | 5 |
| Mechanical shock resistance (IEC/EN 60068-2-27) when tabletop-mounted | | |
| Half-sinusoidal shock, 10 ms | | |
| Main contacts | | |
| N/O contact | g | 10 |
| Auxiliary contacts | | |
| N/O contact | g | 7 |
| N/C contact | g | 5 |
| Degree of Protection | | IP00 |
| Protection against direct contact when actuated from front (EN 50274) | | Finger and back-of-hand proof |
| Altitude | m | Max. 2000 |
| Weight | | |
| AC operated | kg | 0.872 |
| Screw connector terminals | | |
| Terminal capacity main cable | | |
| Solid | mm ² | 1 x (0.75 - 16) 2 x (0.75 - 16) |
| Flexible with ferrule | mm ² | 1 x (0.75 - 35) 2 x (0.75 - 25) |
| Stranded | mm ² | 1 x (16 - 50) 2 x (16 - 35) |
| Solid or stranded | AWG | single 14 - 1, double 14 - 2 |
| Flat conductor | Lamellenzahl x Breite x Dicke | mm 2 x (6 x 9 x 0.8) |
| Stripping length | mm | 14 |
| Terminal screw | | M6 |
| Tightening torque | Nm | 3.3 |
| Tool | | |
| Pozidriv screwdriver | Size | 2 |
| Standard screwdriver | mm | 0.8 x 5.5 1 x 6 |
| Terminal capacity control circuit cables | | |
| Solid | mm ² | 1 x (0.75 - 4) 2 x (0.75 - 2.5) |
| Flexible with ferrule | mm ² | 1 x (0.75 - 2.5) 2 x (0.75 - 2.5) |
| Solid or stranded | AWG | 18 - 14 |
| Stripping length | mm | 10 |
| Terminal screw | | M3.5 |
| Tightening torque | Nm | 1.2 |
| Tool | | |
| Pozidriv screwdriver | Size | 2 |
| Standard screwdriver | mm | 0.8 x 5.5 1 x 6 |

Main conducting paths

| | | | |
|---------------------------------|------------------|------|------|
| Rated impulse withstand voltage | U _{imp} | V AC | 8000 |
|---------------------------------|------------------|------|------|

| | | | |
|--|-------------|------|-------|
| Overvoltage category/pollution degree | | | III/3 |
| Rated insulation voltage | U_i | V AC | 690 |
| Rated operational voltage | U_e | V AC | 690 |
| Safe isolation to EN 61140 | | | |
| between coil and contacts | | V AC | 440 |
| between the contacts | | V AC | 440 |
| Making capacity (p.f. to IEC/EN 60947) | | | |
| | Up to 690 V | A | 560 |
| Breaking capacity | | | |
| 220 V 230 V | | A | 400 |
| 380 V 400 V | | A | 400 |
| 500 V | | A | 400 |
| 660 V 690 V | | A | 250 |
| Short-circuit rating | | | |
| Short-circuit protection maximum fuse | | | |
| Type "2" coordination | | | |
| 400 V | gG/gL 500 V | A | 63 |
| 690 V | gG/gL 690 V | A | 50 |
| Type "1" coordination | | | |
| 400 V | gG/gL 500 V | A | 125 |
| 690 V | gG/gL 690 V | A | 80 |

AC

AC-1

| | | | |
|---|----------------|---|-----|
| Rated operational current | | | |
| Conventional free air thermal current, 3 pole, 50 - 60 Hz | | | |
| Open | | | |
| at 40 °C | $I_{th} = I_e$ | A | 60 |
| at 50 °C | $I_{th} = I_e$ | A | 57 |
| at 55 °C | $I_{th} = I_e$ | A | 55 |
| at 60 °C | $I_{th} = I_e$ | A | 50 |
| enclosed | I_{th} | A | 45 |
| Conventional free air thermal current, 1 pole | | | |
| open | I_{th} | A | 125 |
| enclosed | I_{th} | A | 112 |

AC-3

| | | | |
|---------------------------|-------|-----|---|
| Rated operational current | | | |
| Open, 3-pole: 50 – 60 Hz | | | |
| Notes | | | At maximum permissible ambient temperature (open.) Also tested according to AC-3e. |
| 220 V 230 V | I_e | A | 40 |
| 240 V | I_e | A | 40 |
| 380 V 400 V | I_e | A | 40 |
| 415 V | I_e | A | 40 |
| 440V | I_e | A | 40 |
| 500 V | I_e | A | 40 |
| 660 V 690 V | I_e | A | 25 |
| Motor rating | P | kWh | |
| 220 V 230 V | P | kW | 12.5 |
| 240V | P | kW | 13.5 |
| 380 V 400 V | P | kW | 18.5 |
| 415 V | P | kW | 24 |
| 440 V | P | kW | 25 |
| 500 V | P | kW | 28 |
| 660 V 690 V | P | kW | 23 |
| AC-4 | | | |

| | | | |
|--------------------------|-------|-----|-----|
| Open, 3-pole: 50 – 60 Hz | | | |
| 220 V 230 V | I_e | A | 18 |
| 240 V | I_e | A | 18 |
| 380 V 400 V | I_e | A | 18 |
| 415 V | I_e | A | 18 |
| 440 V | I_e | A | 18 |
| 500 V | I_e | A | 18 |
| 660 V 690 V | I_e | A | 14 |
| Motor rating | P | kWh | |
| 220 V 230 V | P | kW | 5 |
| 240 V | P | kW | 5.5 |
| 380 V 400 V | P | kW | 9 |
| 415 V | P | kW | 9.5 |
| 440 V | P | kW | 10 |
| 500 V | P | kW | 11 |
| 660 V 690 V | P | kW | 12 |

DC

| | | | |
|---------------------------------|-------|---|----|
| Rated operational current, open | | | |
| DC-1 | | | |
| 60 V | I_e | A | 50 |
| 110 V | I_e | A | 50 |
| 220 V | I_e | A | 45 |

Current heat loss

| | | | |
|--|--|-----------|------|
| 3 pole, at I_{th} (60°) | | W | 10.3 |
| Current heat loss at I_e to AC-3/400 V | | W | 6.6 |
| Impedance per pole | | $m\Omega$ | 1.9 |

Magnet systems

| | | | |
|--|----------|--------------|-----------|
| Voltage tolerance | | | |
| AC operated | Pick-up | $\times U_c$ | 0.8 - 1.1 |
| Drop-out voltage AC operated | Drop-out | $\times U_c$ | 0.3 - 0.6 |
| Power consumption of the coil in a cold state and $1.0 \times U_S$ | | | |
| 50 Hz | Pick-up | VA | 149 |
| 50 Hz | Sealing | VA | 16 |
| 50 Hz | Sealing | W | 4.1 |
| 60 Hz | Pick-up | VA | 178 |
| 60 Hz | Sealing | VA | 19 |
| 60 Hz | Sealing | W | 4.1 |
| Duty factor | | % DF | 100 |
| Changeover time at 100 % U_S (recommended value) | | | |
| Main contacts | | | |
| AC operated | | | |
| Closing delay | | ms | 12 - 18 |
| Opening delay | | ms | 8 - 13 |
| Arcing time | | ms | 10 |

Electromagnetic compatibility (EMC)

| | | |
|-----------------------|--|---------------|
| Emitted interference | | to EN 60947-1 |
| Interference immunity | | to EN 60947-1 |

Rating data for approved types

| | | | |
|----------------------|----|----|--|
| Switching capacity | | | |
| Maximum motor rating | | | |
| Three-phase | | | |
| 200 V 208 V | HP | 10 | |
| 230 V 240 V | HP | 15 | |
| 460 V | HP | 30 | |

| | | | |
|--------------------------------------|------|-----------------|--|
| 480 V | | | |
| 575 V | | | |
| 600 V | | | |
| Single-phase | | | |
| 115 V | | | |
| 120 V | | | |
| 230 V | | | |
| 240 V | | | |
| General use | | | |
| Short Circuit Current Rating | SCCR | | |
| Basic Rating | | | |
| SCCR | kA | 10 | |
| max. Fuse | A | 250 | |
| max. CB | A | 250 | |
| 480 V High Fault | | | |
| SCCR (fuse) | kA | 30/100 | |
| max. Fuse | A | 250/150 Class J | |
| SCCR (CB) | kA | 65 | |
| max. CB | A | 100 | |
| 600 V High Fault | | | |
| SCCR (fuse) | kA | 30/100 | |
| max. Fuse | A | 250/150 Class J | |
| SCCR (CB) | kA | 30 | |
| max. CB | A | 250 | |
| Special Purpose Ratings | | | |
| Electrical Discharge Lamps (Ballast) | | | |
| 480V 60Hz 3phase, 277V 60Hz 1phase | A | 79 | |
| 600V 60Hz 3phase, 347V 60Hz 1phase | A | 79 | |
| Incandescent Lamps (Tungsten) | | | |
| 480V 60Hz 3phase, 277V 60Hz 1phase | A | 74 | |
| 600V 60Hz 3phase, 347V 60Hz 1phase | A | 74 | |
| Resistance Air Heating | | | |
| 480V 60Hz 3phase, 277V 60Hz 1phase | A | 79 | |
| 600V 60Hz 3phase, 347V 60Hz 1phase | A | 79 | |
| Elevator Control | | | |
| 200V 60Hz 3phase | HP | 7.5 | |
| 200V 60Hz 3phase | A | 25.3 | |
| 240V 60Hz 3phase | HP | 10 | |
| 240V 60Hz 3phase | A | 28 | |
| 480V 60Hz 3phase | HP | 25 | |
| 480V 60Hz 3phase | A | 34 | |
| 600V 60Hz 3phase | HP | 30 | |
| 600V 60Hz 3phase | A | 32 | |

Design verification as per IEC/EN 61439

| | | | |
|--|-------------------|----|--|
| Technical data for design verification | | | |
| Rated operational current for specified heat dissipation | I _n | A | 40 |
| Heat dissipation per pole, current-dependent | P _{vid} | W | 2.2 |
| Equipment heat dissipation, current-dependent | P _{vid} | W | 6.6 |
| Static heat dissipation, non-current-dependent | P _{vs} | W | 4.1 |
| Heat dissipation capacity | P _{diss} | W | 0 |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 60 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |

| | | |
|--|--|--|
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])

| | | |
|---|----|------------------|
| Rated control supply voltage Us at AC 50Hz | V | 42 - 42 |
| Rated control supply voltage Us at AC 60Hz | V | 48 - 48 |
| Rated control supply voltage Us at DC | V | 0 - 0 |
| Voltage type for actuating | | AC |
| Rated operation current Ie at AC-1, 400 V | A | 60 |
| Rated operation current Ie at AC-3, 400 V | A | 40 |
| Rated operation power at AC-3, 400 V | kW | 18.5 |
| Rated operation current Ie at AC-4, 400 V | A | 18 |
| Rated operation power at AC-4, 400 V | kW | 9 |
| Rated operation power NEMA | kW | 22 |
| Modular version | | No |
| Number of auxiliary contacts as normally open contact | | 0 |
| Number of auxiliary contacts as normally closed contact | | 0 |
| Type of electrical connection of main circuit | | Screw connection |
| Number of normally closed contacts as main contact | | 0 |
| Number of normally open contacts as main contact | | 3 |