

Switch disconnector, low voltage, 160 A, AC 690 V, NH000, AC21B, 3P, IEC, bottom cable terminal, lug terminals



Part no. SIZE 000 HOR FSD - 60MM BUS: M8 SCREWS
Catalog No. EBH00013TBM8

Delivery program

Product range		Fuse accessory
Basic function		Switch disconnector
Field of application		low voltage
Rated current	I	160
Rated voltage		AC 690 V
Construction size		NH000
Utilization category		AC21B
Description		60 mm busbar mounting bottom cable terminal lug terminals M8 screws
Protection		IP20
Number of poles		3P
usable for size/applications		NH000 fuse-links
Standard/Approval		IEC
Standards/Regulations		IEC 60947-1 IEC 60947-3

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Fuse switch disconnector (EC001040)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector (ecl@ss10.0.1-27-37-14-01 [AKF058013])

Version as main switch		No
Version as safety switch		No
Max. rated operation voltage Ue AC	V	690
Rated permanent current Iu	A	160
Rated operation power at AC-23, 400 V	kW	0.064
Conditioned rated short-circuit current Iq	kA	0.1
Rated short-time withstand current Icw	kA	100
Suitable for fuses		NH000
Number of poles		3
With error protection		No
Type of electrical connection of main circuit		Screw connection
Cable entry		Bottom
Equipped with connectors		No
Suitable for floor mounting		No
Suitable for front mounting		No
Suitable for busbar mounting		Yes
Type of control element		Cover grip
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		IP30