

Switch disconnector, low voltage, 250 A, AC 690 V, NH1, AC23B, 3P, IEC, 60 mm busbar mounting, bottom cable terminals, V-clamps

Part no.
Catalog No.

SIZE 1 HOR FSD-60MM BUS:SCREWS
EBH113TBM1

Delivery program

Product range			Fuse accessory
Basic function			Switch disconnector
Field of application			low voltage
Rated current	I	A	250
Rated voltage			AC 690 V
Construction size			NH1
Utilization category			AC23B
Description			60 mm busbar mounting bottom cable terminals V-clamps
Protection			IP30
Number of poles			3P
usable for size/applications			NH1 fuse-links
Standard/Approval			IEC
Standards/Regulations			IEC 60947-1 IEC 60947-3

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Fuse switch disconnector (EC001040)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector (ecl@ss10.0.1-27-37-14-01 [AKF058013])

Version as main switch		No
Version as safety switch		No
Max. rated operation voltage Ue AC	V	690
Rated permanent current Iu	A	250
Rated operation power at AC-23, 400 V	kW	0.1
Conditioned rated short-circuit current Iq	kA	0.08
Rated short-time withstand current Icw	kA	80
Suitable for fuses		NH1
Number of poles		3
With error protection		No
Type of electrical connection of main circuit		Cable clamp
Cable entry		Bottom
Equipped with connectors		No
Suitable for floor mounting		No
Suitable for front mounting		No
Suitable for busbar mounting		Yes
Type of control element		Cover grip
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		IP30