

Thermistor overload relay for machine protection, 1N/O+1N/C, 24-240VAC/DC, without reclosing lockout

EATON
Powering Business Worldwide™

Part no. EMT6-K
Catalog No. 269470
Alternate Catalog No. EMT6-K
EL-Nummer (Norway) 4110423

Delivery program

Product range	EMT6 thermistor overload relay for machine protection		
Function	Without manual reset Mains and fault LED display Trip with short-circuit in the sensor cable Test button		
Rated operational current			
AC-15			
240 V	I_e	A	3
AC-14			
300 V	I_e	A	3
400 V	I_e	A	3
			Value applies starting with release 001.
conventional thermal current	I_{th}	A	6
Rated control voltage	U_s	V	24 - 240 V 50 - 400 Hz 24 - 240 V DC

Notes



BVS 14 ATEX F003 X

II(2)G [Ex e] [Ex d] [Ex px]

II(2)D [Ex t] [Ex p]

Observe manual MN03407006Z-DE/EN.

Can be snap fitted on a top-hat rail to IEC/EN 60715.

Technical data

General

Standards	IEC/EN 60947, VDE 0660, EN 55011		
Climatic proofing	Damp heat, constant, to IEC 60068-2-78; Damp heat, cyclic, to IEC 60068-2-30		
Ambient temperature			
Open	°C	-25 - +60	
Enclosed	°C	-25 - 45	
Storage	°C	-45 - 85	
Mounting position		As required	
Weight	kg	0.15	
Mechanical shock resistance half-sinusoidal shock 10 ms to IEC 60068-2-27	g	10	
Degree of Protection		IP20	
Protection against direct contact when actuated from front (EN 50274)		Finger and back-of-hand proof	
Safe isolation to EN 61140			
between the contacts	V AC	250	
between contacts and power supply	V AC	250	

Auxiliary and control circuits

Rated impulse withstand voltage	U_{imp}	V AC	4000
---------------------------------	-----------	------	------

Rated impulse withstand voltage	U_{imp}	V AC	6000
			Value applies starting with release 001.
Overvoltage category/pollution degree	III/3		
Terminal capacities Auxiliary and control circuits			
Solid	mm^2	1 x (0.5 - 2.5) 2 x (0.5 - 1.5)	
Flexible with ferrule	mm^2	1 x (0.5 - 2.5) 2 x (0.5 - 1.5)	
Solid or stranded	AWG	20 - 14	
Terminal screw		M3.5	
Tightening torque	Nm	1.2	
Tools			
Pozidriv screwdriver	Size	2	
Standard screwdriver	mm	1 x 6	

Auxiliary power circuit

Rated insulation voltage	U_i	V	300
Rated insulation voltage	U_i	V	400
			Value applies starting with release 001.
Rated operational current	I_e	A	
AC--14			
Make contact			
300 V	I_e	A	3
380 V 400 V 415 V	I_e	A	3
			Value applies starting with release 001.
Break contact			
300 V	I_e	A	3
380 V 400 V 415 V	I_e	A	3
			Value applies starting with release 001.
AC-15			
Make contact			
220 V 230 V 240 V	I_e	A	3
300 V	I_e	A	1
380 V 400 V 415 V	I_e	A	1
			Value applies starting with release 001.
Break contact			
220 V 230 V 240 V	I_e	A	3
300 V	I_e	A	1
380 V 400 V 415 V	I_e	A	1
			Value applies starting with release 001.
Max. short-circuit protective device			
Fuse	gG/gL	A	6

Control circuit

Rated insulation voltage	U_i	V	240
Rated operational voltage	U_e	V	240
Pick-up and drop-out values		$\times U_e$	0.85 - 1.1
Power consumption			
AC		VA	3.5
DC		W	2
Trip at approx.		Ω	3600
Recovery at approx.		Ω	1600
Sensor circuit			Sensor circuit parameters at U_S and +20 °C: max. Cable length to sensor 250m (not insulated) Total cold resistance $\sum R_K \leq 1500 \Omega$ - R_{T1-T2} (T1, T2 shorted): $I_{T1-T2} = 1.9 \text{ mA}$ - R_{T1-T2} (4 kΩ): $U_{T1-T2} = \text{max. } 3 \text{ V DC}$, $I_{T1-T2} = \text{max. } 0.8 \text{ mA}$ - R_{T1-T2} (T1, T2 open): $U_{T1-T2} = 5.1 \text{ V DC typ.}$ (5.5 V DC max.)

Electromagnetic compatibility (EMC)

Electrostatic discharge (ESD)			
applied standard			IEC/EN 61000-4-2
Air discharge	kV	8	
Contact discharge	kV	6	
Electromagnetic fields (RFI)			
applied standard			IEC/EN 61000-4-3
	V/m	80 - 1000 MHz: 10 1.4 - 2 GHz: 3 2.0 - 2.7 GHz: 1	
Radio interference suppression			EN 55011 Class B
Burst	kV	Supply cables: 2 Signal cables: 1 according to IEC/EN 61000-4-4	
power pulses (Surge)		2 kV (symmetrical) 4 kV (asymmetrical) according to IEC/EN 61000-4-5	
Immunity to line-conducted interference to (IEC/EN 61000-4-6)	V	10	

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I _h	A	0
Heat dissipation per pole, current-dependent	P _{vid}	W	0
Equipment heat dissipation, current-dependent	P _{vid}	W	0
Static heat dissipation, non-current-dependent	P _{vs}	W	0.8
Heat dissipation capacity	P _{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	60

Technical data ETIM 8.0

Relays (EG000019) / Temperature monitoring relay (EC001446)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Monitoring equipment (low-voltage switch technology) / Temperature monitoring equipment (ecl@ss10.0.1-27-37-18-10 [AKF104014])		
Type of electric connection		Screw connection
Rated control supply voltage Us at AC 50Hz	V	24 - 240
Rated control supply voltage Us at AC 60Hz	V	24 - 240
Rated control supply voltage Us at DC	V	24 - 240
Voltage type for actuating		AC/DC
With detachable clamps		No
Number of measuring circuits		1
Error registration possible		No
External reset possible		No
Number of contacts as normally closed contact		1
Number of contacts as normally open contact		1
Number of contacts as change-over contact		0
Temperature measuring range	°C	0 - 0
Resistance measuring range	Ohm	750 - 12000
Width	mm	23
Height	mm	83
Depth	mm	103