

## Contact expansion module, 24VDC/AC, 5 enabling paths



**Part no.** **ESR5-NE-51-24VAC-DC**  
**Catalog No.** **118707**  
**EL-Nummer** **4133324**  
**(Norway)**

## Delivery program

Product range			Electronic safety relays
Basic function			Contact expansions
<b>Features</b>			
Mounting width		mm	22.5
Operation			Basic isolation
Supply voltage	U <sub>s</sub>		single-channel
Safety related characteristics			24 V DC 24 V AC, 50/60 Hz
			Cat. 4 PL e according to EN ISO 13849-1 SILCL 3 according to IEC 62061 SIL 3 according to IEC 61508
<b>Number of enabling paths to EN 60204-1 Stop functions category</b>			
Enable current paths to IEC/EN 60204-1 Stop category 0			5
Signal current paths			1
<b>Instructions</b>			The base unit determines the maximum stop category according to IEC 61508 and IEC 60204.

## Technical data

<b>General</b>			
Intended use			Safety relay contact expansion block per DIN EN60204-1/VDE 0113 Part 1 for contact multiplication. The expansion unit can be used for contact multiplication for emergency stop relays and two-hand controls.
Policies List			EMV 2004/108/EG, Maschinen 2006/42/EG
Standards			EN ISO 13849-1:2008, EN 62061:2005+AC:2010, EN 61508, Parts 1-7:2001, EN 50178:1997, EN 60204-1:2006+A1:2009
Dimensions (W x H x D)	mm		22.5 x 99 x 114.5
Mounting width	mm		22.5
Weight	kg		0,22
Mounting position			As required
Mounting			Top-hat rail IEC/EN 60715, 35 mm
Connection type			M3 screw terminals
Lifespan, mechanical	Operations	x 10 <sup>6</sup>	10
Terminal capacity			
Solid	mm <sup>2</sup>		1x (0.2 – 2.5) 2x (0.2 – 1)
Flexible with ferrule	mm <sup>2</sup>		1x (0.25 – 2.5) 2x (0.25 – 1)
Solid or stranded	AWG		24 - 12
Terminal screw	Nm		
Pozidriv screwdriver	Size		2
Standard screwdriver	mm		0.6 x 3.5
Max. tightening torque	Nm		0.6
Stripping length	mm		7
Material			Housing: polyamide PA not reinforced Contacts: Material: silver tin oxide, gold plated (AgSnO <sub>2</sub> , 0.2 µm Au)
Duty factor	% DF		100

Operating conditions			
Climatic environmental conditions			
Climatic proofing			Dry heat to IEC 60068-2-2 Damp heat as per EN 60068-2-3
Ambient temperature			
Operation	9	°C	-20 - +55
Storage	9	°C	-40 - +70
Condensation			Non-condensing
Atmospheric conditions			
relative humidity		%	Max. 75
Air pressure (operation)		hPa	795 - 1080
Altitude	Above sea level	m	2000
Power loss	P	W	5.8

### Ambient conditions, mechanical

Degree of protection to VDE 0470-1					
Enclosures			IP20		
Terminals			IP20		
Degree of Protection			Installation location: ≥ IP54		
B10d [switching cycles]			230000		
Protection against direct contact when actuated from front (EN 50274)					
Vibrations (IEC/EN 60068-2-6)					
Clearance in air and creepage distances			EN 50178, UL 508, CSA C22.2, No. 14-95		
Rated impulse withstand voltage	U <sub>imp</sub>	V AC	4000		
Insulation			Basic isolation Safe isolation, reinforced insulation and 6 kV between A1/A2, 11/12, 23/24, 71/72 and 33/34, 43/44, 53/54, 63/64.		
Overvoltage category/pollution degree			III/2		
Stop category	according to EN60204-1		1,02		
Technical safety parameters:					
Values according to EN ISO 13849-1					
Performance level	according to EN ISO 13849-1		PL e		
Category	according to EN ISO 13849-1		Kat. 4		
Safety integrity level claim limit	in accordance with 62061		SILCL 3		
Safety integrity level	In accordance with IEC 61508		SIL 3		
Probability of failure per hour	PFH <sub>d</sub>	x 10 <sup>-10</sup>	1.02		
Prooftest High Demand		Months	240		
Prooftest Low Demand		Months	84		
Rated operational voltage	U <sub>e</sub>	V AC	230		
Rated operational voltage	U <sub>e</sub>	V	24 V AC, 24 V DC		
Permissible range			0.85 - 1.1 x U <sub>e</sub>		
Rated insulation voltage	U <sub>i</sub>	V AC	250		
Quadratic summation current		A <sup>2</sup>	72 A <sup>2</sup> (I <sub>TH</sub> <sup>2</sup> = I <sub>1</sub> <sup>2</sup> + I <sub>2</sub> <sup>2</sup> + I <sub>3</sub> <sup>2</sup> + I <sub>4</sub> <sup>2</sup> + I <sub>5</sub> <sup>2</sup> )		
Notes			Observe derating curve → Engineering		
Inrush current		A	min - max 0.025 - 6		
Minimum switching capacity		W	0.4		

### Control circuit

Power supply circuit			
AC operated 50/60 Hz		W	2.2
DC operated		W	2.2

## Input data

Rated current		mA	A1, A2:92
Current consumption		mA	AC: 92 DC: 92
Pick-up time (K1, K2) for UN automatic mode, typical	t <sub>A</sub>	ms	20
Pick-up time (K1, K2) for UN manual operation, typical	t <sub>A</sub>	ms	20
Pick-up time		ms	at Ue in automatic mode: normally 20 at Ue in manual mode: normally 20
Reset time (K1, K2) for U <sub>N</sub> , normally	t <sub>R</sub>	ms	20
Simultaneity for inputs 1/2	t <sub>sync</sub>	ms	∞
Maximum switching frequency		Hz	0.5
Status indication			Green LED

## Output data

Contact type			
Non-delayed enable current paths			5
Delayed signal current path			1
Feedback current path			1
Switching voltage			min – max 15 - 250 V AC 15 - 250 V DC
Limiting continuous current	A		per N/O: 6 N/C: 3
Short-circuit protection for output circuits, external			Fuse 6 A gL/gG
Output fuse			
fast			6
Miniature circuit-breaker (24 VAC/VDC)			C6
Maximum breaking power			
Resistive load (τ = 0 ms)			
24 V DC	W		144
Notes			for N/C contact 11/12 71/72
48 V DC	W		288
Notes			for N/C contact 11/12 71/72
110 V DC	W		110
220 V DC	W		88
250 V AC	VA		1500
Notes			for N/C contact 11/12 71/72
Inductive load (τ = 40 ms)			
24 V DC	W		42
48 V DC	W		42
110 V DC	W		42
220 V DC	W		42
Switching capacity			In accordance with IEC 60947-5-1
AC-15			
230 V	A		4 A bei 360 S/h 3 A bei 3600 S/h
DC-13			
24 V	A		4 A bei 360 S/h 2.5 A bei 3600 S/h
Further information (flip catalog)			description

## Electromagnetic compatibility (EMC)

Emitted interference			In accordance with EN 61000-6-4
Interference immunity			according to EN 61000-6-2

## Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I <sub>n</sub>	A	0
Heat dissipation per pole, current-dependent	P <sub>vid</sub>	W	0
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	0

Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	5.8
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature min.		°C	-20
Operating ambient temperature max.		°C	55
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 8.0

Relays (EG000019) / Device for monitoring of safety-related circuits (EC001449)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Monitoring equipment (low-voltage switch technology) / Device for monitoring of safety-related circuits (ecl@ss10.0.1-27-37-18-19 [AC0304011])

Model		Expansion device
Suitable for monitoring of position switches		Yes
Suitable for monitoring of emergency-stop circuits		Yes
Suitable for monitoring of valves		No
Suitable for monitoring of optoelectronic protection equipment		No
Suitable for monitoring of tactile sensors		No
Suitable for monitoring of magnetic switches		No
Suitable for monitoring of proximity switches		No
Type of electric connection		Screw connection
Rail mounting possible		Yes
Rated control supply voltage Us at AC 50Hz	V	0 - 26.4
Rated control supply voltage Us at AC 60Hz	V	20.4 - 24
Rated control supply voltage Us at DC	V	0 - 24
Voltage type for actuating		AC/DC
With detachable clamps		Yes
Evaluation inputs		1-channel
With start input		No
With muting function		No
With feedback circuit		Yes

Release-delay	s	0 - 0
Number of outputs, safety related, undelayed, with contact		5
Number of outputs, safety related, delayed, with contact		0
Number of outputs, safety related, undelayed, semiconductors		0
Number of outputs, safety related, delayed, semiconductors		0
Number of outputs, signalling function, undelayed, with contact		1
Number of outputs, signalling function, delayed, with contact		0
Number of outputs, signalling function, undelayed, semiconductors		0
Number of outputs, signalling function, delayed, semiconductors		0
Type of safety according to IEC 61496-1		None
Stop category according to IEC 60204		0
Performance level according to EN ISO 13849-1		Level e
SIL according to IEC 61508		3
With approval for BG BIA		No
With approval according to UL		Yes
Width	mm	22.5
Height	mm	99
Depth	mm	114.5
With approval for TÜV		Yes