

Data sheet

6GK1901-1BB10-2AB0

product type designation	IE FC RJ45 Plug 180 (2x2)
product description	RJ45 data connector
	Industrial Ethernet FastConnect RJ45 plug 180 2x 2, RJ45 plug-in connector (10/100 Mbit/s) with rugged metal enclosure and FC connection system, for IE FC TP cable 2x 2; 180° cable outlet 1 pack = 10 units.
	
suitability for use	For connection to IE FC TP cables 2x2, suitable for fast assembly with the FastConnect system
transfer rate	
transfer rate / for Industrial Ethernet	10 Mbit/s, 100 Mbit/s
interfaces	
number of electrical connections	
• for Industrial Ethernet FC TP cables	4
• for network components or terminal equipment	1
type of electrical connection	
• for Industrial Ethernet FC TP cables	integrated cut-and-clamp contacts for 4-wire TP FC installation cable AWG22
• for network components or terminal equipment	RJ45 connector
type of electrical connection / FastConnect	Yes
mechanical data	
material / of the enclosure	metal
number of reuses	10
locking mechanism design	other
design, dimensions and weights	
type of cable outlet	180° cable outlet
width	13.7 mm
height	16 mm
depth	55 mm
net weight	35 g
connectable cable cross-section	6.5 ... 6.5 mm
connectable conductor cross-section	0.33 mm ²
ambient conditions	
ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
product features, product functions, product components / general	
product feature	
• PoE capability	Yes
• PoE+capability	Yes
• silicon-free	Yes

product component	Yes
• strain relief	
standards, specifications, approvals	
certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
• cULus approval	Yes
• railway application in accordance with EN 50155	No
standard for structured cabling	Cat5
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
Global Warming Potential [CO2 eq]	
• total	0.277 kg
• during manufacturing	0.263 kg
• during operation	0.0086 kg
• after end of life	0.0062 kg
further information / internet links	
internet link	
• to website: Image database	https://www.automation.siemens.com/bilddb
• to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial security concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial security measures that may be implemented, please visit https://www.siemens.com/industrialsecurity. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Security RSS Feed under https://www.siemens.com/cert. (V4.6)</p>

last modified:

2/15/2024 