

Data sheet

6XV1840-2AU10

product description



Standard bus cable (4 wires), preferred length, not assembled

Industrial Ethernet FC TP standard cable GP, TP installation cable for connection to IE FC RJ45 2x2, for universal use, shielded Cat5e, 1000 m.

suitability for use

Standard cable with rigid cores for fast installation

cable designation

2YY (ST) CY 2x2x0,64/1,5-100 GN SF/UTP

wire length

1000 m

electrical data

attenuation factor per length

- at 10 MHz / maximum 0.052 dB/m
- at 100 MHz / maximum 0.195 dB/m

impedance

- at 1 MHz ... 100 MHz 100 Ω

relative symmetrical tolerance

- of the characteristic impedance at 1 MHz ... 100 MHz 15 %

transfer impedance per length / at 10 MHz

10 mΩ/m

loop resistance per length / maximum

115 mΩ/m

operating voltage

- RMS value 80 V

NVP value in percent

69 %

mechanical data

number of electrical cores

4

design of the shield

Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires

type of electrical connection / FastConnect

Yes

core diameter

- of AWG22 insulated conductor 0.64 mm

outer diameter

- of inner conductor 0.64 mm
- of the wire insulation 1.5 mm
- of the inner sheath of the cable 3.9 mm
- of cable sheath 6.5 mm

symmetrical tolerance of the outer diameter / of cable sheath

0.2 mm

material

- of the wire insulation polyethylene (PE)
- of the inner sheath of the cable PVC
- of cable sheath PVC

color

- of the insulation of data wires white/yellow/blue/orange
- of cable sheath green

bending radius

- with single bend / minimum permissible 19.5 mm
- with multiple bends / minimum permissible 49 mm

| | |
|--------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tensile load / maximum | 150 N |
| weight per length | 61 kg/km |
| ambient conditions | |
| ambient temperature | <ul style="list-style-type: none"> • during operation -40 ... +75 °C • during storage -40 ... +75 °C • during transport -40 ... +75 °C • during installation -40 ... +60 °C • note Electrical properties measured at 20 °C, tests according to DIN VDE 0472 |
| fire behavior | flame resistant according to IEC 60332-3-24 (Category C) and UL 1685 (CSA FT 4) |
| class of burning behaviour / according to EN 13501-6 | Eca |
| chemical resistance | <ul style="list-style-type: none"> • to mineral oil oil resistant according to IEC 60811-2-1 (4 h / 70°C) • to grease Conditional resistance • to water conditional resistance |
| radiological resistance / to UV radiation | resistant |
| product features, product functions, product components / general | |
| product feature | <ul style="list-style-type: none"> • halogen-free No • silicon-free Yes |
| wire length / for Industrial Ethernet | 100 m |
| standards, specifications, approvals | |
| UL/ETL listing / 300 V Rating | Yes; c(ETL)us / CMG / (ETL)us PLTC/ ITC / Sun Res |
| UL/ETL style / 600 V Rating | Yes; cRUs AWM 21694 AWM I A/B 60°C 600V FT2 |
| certificate of suitability | <ul style="list-style-type: none"> • EAC approval Yes • CE marking Yes |
| standard for structured cabling | Cat5e |
| Marine classification association | <ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) No • French marine classification society (BV) No • Det Norske Veritas (DNV) No • Germanische Lloyd (GL) No • Lloyds Register of Shipping (LRS) No • Nippon Kaiji Kyokai (NK) No • Polski Rejestr Statków (PRS) No |
| reference code | <ul style="list-style-type: none"> • according to IEC 81346-2 WG • according to IEC 81346-2:2019 WGB |
| further information / internet links | |
| internet link | <ul style="list-style-type: none"> • to website: Image database https://www.automation.siemens.com/bilddb • to website: Industry Online Support https://support.industry.siemens.com |
| security information | |
| security information | <p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p> |

Approvals / Certificates

General Product Approval

Test Certificates

[Manufacturer Declaration](#)



[Declaration of Conformity](#)



[Manufacturer Declaration](#)

[Special Test Certificate](#)

other

Environment

Industrial Communication

[Manufacturer Declaration](#)

[Confirmation](#)

[Confirmation](#)



[PROFINET](#)

last modified:

3/25/2024