

**Housing, Emergency stop/emergency switching off pushbutton,
Mushroom-shaped, 38 mm, Non-illuminated, Key-release, 1 NC, 1 N/O,
Screw connection, Red (RAL 3000), Yellow**



Part no. M22-PVS/KC11/IY
Catalog No. 216523
Alternate Catalog No. M22-PVS-KC11-IYQ
EL-Nummer (Norway) 4355296

Delivery program

| | | | |
|---|------|----|---|
| Product range | | | RMQ-Titan |
| Basic function | | | Housing Controlled stop pushbuttons/emergency-stop buttons |
| Mounting hole diameter | Ø | mm | 22.5 |
| Single unit/Complete unit | | | Complete unit |
| Design | | | Mushroom-shaped |
| Diameter | Ø | mm | 38 |
| Illumination | | | Non-illuminated |
| Connection type | | | Key-release |
| Description | | | Screw connection |
| Number of locations | Qty. | | Tamper-proof according to ISO 13850/EN 418 Not suitable for master key systems |
| Colour | | | |
| Mushroom head | | | Red |
| Enclosure covers | | | Yellow |
| RAL Value | | | RAL 3000 |
| Degree of Protection | | | IP66, IP67, IP69 |
| Connection to SmartWire-DT | | | no |
| Contacts | | | |
| N/C = Normally closed | | | 1 NC |
| N/O = Normally open | | | 1 N/O |
| Notes | | | = safety function, by positive opening to IEC/EN 60947-5-1 |
| Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1 | | | |
| | mm | | 4.8 |
| Maximum travel | mm | | 5.7 |
| Minimum force for positive opening | N | | 20 |
| Positive opening (ZW) | | | yes |
| Information about equipment supplied | | | 1 key included as standard |

Technical data

| | | | |
|----------------------|------------|---------------|--|
| General | | | |
| Standards | | | IEC/EN 60947 VDE 0660 |
| Lifespan, mechanical | Operations | $\times 10^6$ | > 0.1 |
| Operating frequency | | Operations/h | ≤ 600 |
| Actuating force | | n | ≤ 50 |
| Climatic proofing | | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Degree of Protection | | | IP66, IP67, IP69 |
| Ambient temperature | | °C | -25 - +70 |
| Open | | | |
| Mounting position | | | As required |

| | | |
|-----------------------------|---|---|
| Mechanical shock resistance | g | 50 Shock duration 11 ms Sinusoidal according to IEC 60068-2-27 |
| shipping classification | | DNV GL LR |

Contacts

| | | | |
|---|----------------|----|---|
| Rated conditional short-circuit current | I _q | kA | 1 |
|---|----------------|----|---|

Design verification as per IEC/EN 61439

| | | | |
|--|-------------------|----|--|
| Technical data for design verification | | | |
| Rated operational current for specified heat dissipation | I _n | A | 6 |
| Heat dissipation per pole, current-dependent | P _{vid} | W | 0.11 |
| Equipment heat dissipation, current-dependent | P _{vid} | W | 0 |
| Static heat dissipation, non-current-dependent | P _{vs} | W | 0 |
| Heat dissipation capacity | P _{diss} | W | 0 |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 70 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Please enquire |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 8.0

| | |
|---|---|
| Low-voltage industrial components (EG000017) / Control circuit devices combination in enclosure (EC000225) | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Command and alarm device combination in housing (ecl@ss10.0.1-27-37-12-16 [AKF034014]) | |
| Number of command positions | 1 |
| Number of push buttons | 0 |
| Number of indicator lights | 0 |
| Number of key switches | 0 |
| Number of selector switches | 0 |
| Number of mushroom-shaped push-buttons | 1 |

| | | |
|---|---|------------|
| Suitable for emergency stop | | Yes |
| Rated control supply voltage Us at AC 50HZ | V | 115 - 500 |
| Rated control supply voltage Us at AC 60HZ | V | 115 - 500 |
| Rated control supply voltage Us at DC | V | 24 - 220 |
| Colour housing cover | | Yellow |
| Material housing | | Plastic |
| Number of contacts as normally open contact | | 1 |
| Number of contacts as normally closed contact | | 1 |
| Number of contacts as change-over contact | | 0 |
| Degree of protection (IP) | | IP67/IP69K |
| Degree of protection (NEMA) | | 4X, 13 |