

Label, emergency switching off, yellow, blank

Part no.	M22-XBK
Catalog No.	269580
Alternate Catalog No.	M22-XBKQ
EL-Nummer	4315306
(Norway)	

Delivery program

Product range	Accessories
Basic function accessories	Emergency-stop labels
Form	Diameter = 60 mm
Name	Blank
Colour	yellow
RAL Value	RAL 1004
Degree of Protection	IP66
Connection to SmartWire-DT	no

Technical data

General

Degree of Protection	IP66
Ambient temperature	
Open	°C -25 - +70
shipping classification	DNV GL LR

Design verification as per IEC/EN 61439

Technical data for design verification	
Rated operational current for specified heat dissipation	I _n A 0
Heat dissipation per pole, current-dependent	P _{vid} W 0
Equipment heat dissipation, current-dependent	P _{vid} W 0
Static heat dissipation, non-current-dependent	P _{vs} W 0
Heat dissipation capacity	P _{diss} W 0
Operating ambient temperature min.	°C -25
Operating ambient temperature max.	°C 70
IEC/EN 61439 design verification	
10.2 Strength of materials and parts	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9 Insulation properties	

10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Text plate for command devices (EC000624)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss10.0.1-27-37-12-25 [AKF043014])

Meaning of the imprint		None
Language of the imprint		Other
Imprint ISO symbols		None
Colour		Yellow
Shape		Round
Width	mm	60
Height	mm	1
Outer diameter	mm	60