

Remote operator, 220-250VDC, standard

Part no. **NZM2-XRD220-250DC**
 Catalog No. **115395**



Powering Business Worldwide™

Similar to illustration

Delivery program

Product range				Accessories
Accessories				Remote operator, standard
Rated operating frequency				DC
Standard/Approval				UL/CSA, IEC
Construction size				NZM2
Description	<p>For remote switching of circuit-breakers and switch-disconnectors.</p> <p>ON and OFF switching and resetting by means of two-wire or three-wire control.</p> <p>Local switching by hand possible.</p> <p>Lockable in the 0 position of the remote operator with up to 3 padlocks (hasp thickness: 4 – 8 mm)</p>			
	<p>Three-wire control</p> <p>Two-wire control</p> <p>Three-wire control with automatic reset to the 0 position after the switch has tripped</p> <p>Switching cycle:</p> <p>Parallel remote operator connection</p>			<p>Please note during engineering:</p> <p>Terminal 70/71: NZM-XR: Contact loading according to technical data NZM2-XRD: Full current flows through the contact during make and break! RMQ series contact elements can be used for the NZM2(3.4)-XR(D)...remote operators.</p> <p>Terminal 75: NZM-XR: Operational readiness signal when cover closed and not locked. NZM2-XRD: Operational readiness signal when sliding switch set to Auto. Sliding switch with three positions: Manual/Auto/Locked for reliable differentiation of connected positions. AC-15: 400 V; 2 A DC-13: 220 V; 0.2 A</p>
Closing delay	ms	110 – 170		
Break time	ms	110 – 170		
Rated control voltage	U _s	220 - 250 V DC		
Number of poles		3/4 pole		
For use with		NZM2(-4) N(S)2(-4)		
Project planning information		<p>Sliding switch for "Auto" or "Manual"</p> <p>Max. number auxiliary contacts: 2 standard auxiliary contacts, 1 trip-indicating auxiliary switches</p> <p>Cannot be combined with switch-disconnector PN...</p> <p>Cannot be combined with mechanical interlock</p>		

Technical data

Remote operator

Rated control voltage	U _s	V	
DC	U _s	V DC	220 - 250
Operating range		x U _s	0.85 - 1.1
AC		x U _s	0.85 - 1.1
DC			
Motor rating			
DC			
24 V ... 30 V DC	P	W	450
Minimum signal duration			
with switch on	ms	100	
with switch off	ms	100	
Lifespan, mechanical	Operations		20000
Maximum operating frequency		Ops./h	
Max. operating frequency		Ops/h	120
Terminal capacities		mm ²	
Solid or flexible conductor, with ferrule		mm ²	0,75 - 2,5
		AWG	18 ... 14

Design verification as per IEC/EN 61439

IEC/EN 61439 design verification		
10.2 Strength of materials and parts		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9 Insulation properties		
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Type of switch drive	Motor drive	
Rated control supply voltage Us at AC 50HZ	V	0 - 0
Rated control supply voltage Us at AC 60HZ	V	0 - 0
Rated control supply voltage Us at DC	V	220 - 250
Voltage type for actuating		DC