
PRODUCT-DETAILS

OT16F3

OT16F3 SWITCH-DISCONNECTOR



General Information

Extended Product Type	OT16F3
Product ID	ISCA104811R1001
EAN	6417019389554
Catalog Description	OT16F3 SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, base mounted, DIN-rail mountable switch-diconnector / non-fusible diconnect switch with protected clamp terminals, handle and shaft are not included

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	ISCC301020C0201
Instructions and Manuals	ISCC301052M0006
Mechanical Drawings	ISCC301434F0001 ISCC301433F0001 OT16-40F3.stp

Dimensions

Product Net Width	35 mm
Product Net Height	68 mm
Product Net Depth / Length	56 mm
Product Net Weight	0.09 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 16 A (500 V) 16 A (690 V) 16 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 16 A (500 V) 16 A (690 V) 16 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 16 A (500 V) 16 A (690 V) 10 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 3 kW (400 ... 415 V) 7.5 kW (500 V) 7.5 kW (690 V) 7.5 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40 \text{ } ^\circ\text{C} 25 \text{ A}$
Conventional Thermal Current (I_{the})	Fully Enclosed 25 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 0.71 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 0.5 kA
Rated Conditional Short- Circuit Current (I_{nc})	(40 A fuse, $\leq 415\text{V}$) 50 kA (25 A fuse, 690 V) 50 kA
Power Loss	at Rated Operating Conditions per Pole 0.3 W
Pollution Degree	3
Handle Type	Knob Handle and shaft not included
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3 / UL 508 / CSA C22.2 No. 14
Special Functions	No

Mounting Type	Base mounting
Number of Poles	3
Cable Cross-Section	Cu 0.75 ... 10 mm ²
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 0.8 N·m
Mechanical Durability	20000
Lock Type	No

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	20 A
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 1 Hp (240 V AC) Single Phase 2 Hp (440 ... 480 V AC) Single Phase 5 Hp (550 ... 600 V AC) Single Phase 7.5 Hp (220 ... 240 V AC) Three Phase 5 Hp (440 ... 480 V AC) Three Phase 10 Hp (550 ... 600 V AC) Three Phase 10 Hp
Tightening Torque	acc. IEC 60947-1 0.8 N·m
Tightening Torque UL/CSA	7 in·lb

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	1SCC301262D0201

Certificates and Declarations (Document Number)

ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC301166D2703
Environmental Information	1SCC301262D0201
Instructions and Manuals	1SCC301052M0006
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
UL Certificate	cULus certificate OT16-80
VDE Certificate	No certification needed

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	67 mm
Package Level 1 Depth / Length	79 mm
Package Level 1 Height	46 mm
Package Level 1 Gross Weight	0.1 kg

Package Level 1 EAN

6417019389554

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
UNSPSC	39122233
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601419
E-Number (Sweden)	3170937

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

