

PRODUCT-DETAILS

OTM160E4CM24D

OTM160E4CM24D MOTORIZED C/O SWITCH



General Information

Extended Product Type	OTM160E4CM24D
Product ID	1SCA022846R0860
EAN	6417019296760
Catalog Description	OTM160E4CM24D MOTORIZED C/O SWITCH
Long Description	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Include a storage clip for the handle and spare fuses.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303002M0204

Dimensions

Product Net Width	307 mm
Product Net Height	150 mm
Product Net Depth / Length	197 mm

Product Net Weight	5 kg
--------------------	------

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-31B (I_e)	(380 ... 415 V) 160 A
Rated Operational Current AC-33B (I_e)	(380 ... 415 V) 160 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 90 kW (500 V) 110 kW (690 V) 160 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40\text{ °C}$ 160 A
Conventional Thermal Current (I_{the})	Fully Enclosed 160 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 8 kiloampere rms
Motor Operational Voltage	24 V DC
Power Loss	2.4 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP20
Transition Type	Open

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	1SCC303036D0202

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303031D0201
Environmental Information	1SCC303036D0202
Instructions and Manuals	1SCC303002M0204
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	212 mm
Package Level 1 Depth / Length	389 mm
Package Level 1 Height	219 mm
Package Level 1 Gross Weight	6.4 kg
Package Level 1 EAN	6417019296760

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641707

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Motorized Change-over Switches

