

PRODUCT-DETAILS

OVR T2 40-275 P QS

OVR T2 40-275 P QS Surge Protective Device



General Information

Extended Product Type	OVR T2 40-275 P QS
Product ID	2CTB803871R2300
EAN	3660308519580
Catalog Description	OVR T2 40-275 P QS Surge Protective Device
Long Description	Surge protective devices SPD type 2 protect low-voltage consumer systems against surge voltages as they are tested as SPD type 2 according to IEC 61643-11. The devices are compatible with the System pro M compact series. The SPD with "TS" are optionally equipped with a auxiliary contact.

Technical

Standards	IEC 61643-11 / EN 61643-11
Type of Low Voltage Distribution System	TT TN-C TN-S
Suitable For	To protect the systems against the transient overvoltage (lightning)
Rated Voltage (U_r)	230 V AC
Nominal AC Voltage of the System (U_o)	230 / 400 V
Voltage Rating DC	350 V
Voltage Protection Level (U_p)	1.25 kV (L-N) 1.25 kV (N-PE) 1.25 kV (L-PE) 1.25 kV
Maximum Continuous	(L-PE) 275 V (L-L) 275 V

Operating Voltage (U _c)	(L-N) 275 V (N-PE) - V
Temporary Overvoltage Test Value (U _T)	337 V
Rated Service Short- Circuit Breaking Capacity (I _{cs})	100 kA
Discharge Current	Nominal 20 kA Maximum 40 kA Total 40 kA Nominal (8 / 20 μs) 20 kA I (max, 8 / 20 μs) 40 kA
Impulse Current	I (imp, 10 / 350 μs) 2 kA
Short Circuit Withstand I _{cc}	100 kA
Power Loss	8 mW
Short-Circuit Protective Devices	Curve B Breakers ≤ 125 A Curve C Breakers ≤ 125 A gL Type Fuses ≤ 125 A gG Type Fuses ≤ 125 A
Arrester Class	II
Number of Poles	1
Number of Protected Poles	1
Number of Conductors	1
Transmission Standard	Optic
Version	Plug-in
Mounting Type	DIN rail (top hat rail) 35 mm
Product Type	QS
Options Provided	Residential, commercial building.
Auxiliary Circuit Load	Minimum - Maximum -
Preventive Maintenance Feature	No
Status Indicator	Yes
Fuse Size	1 modular spacing

Environmental

Degree of Protection	IP20
Maximum Operating Altitude Permissible	Without Derating 5000
RoHS Status	Following EU Directive 2011/65/EU

Dimensions

Width in Number of Modular Spacings	1
Product Net Width	17.8 mm
Product Net Height	88 mm
Product Net Depth / Length	58 mm
Product Net Weight	0.12 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	117 mm
Package Level 1 Height	82 mm

Package Level 1 Depth / Length	25 mm
Package Level 1 Gross Weight	145 g
Package Level 1 EAN	3660308519580

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
E-Number (Finland)	3211204
Country of Origin	Bulgaria (BG)

Certificates and Declarations (Document Number)

CB Certificate	2CTC432024G1701
CQC Certificate	9AKK107680A1974
Declaration	2CTC432056G1701
Declaration of Conformity - CE	9AKK108466A4410
Instructions and Manuals	2CTC432097M1701
RoHS Information	9AKK108466A4410

Popular Downloads

Data Sheet, Technical Information	2CTC432208D0201
Instructions and Manuals	2CTC432097M1701
Mechanical Drawings	2CTC800021F0100.pdf 2CTC800021F0101.dxf 2CTC800021F0102.stp 2CTC800021F0103.igs

Classifications

ETIM 7	EC000941 - Surge protection device for power supply systems
ETIM 8	EC000941 - Surge protection device for power supply systems
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363090
eClass	V11.0 : 27130805
Object Classification Code	141DCC

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs → Surge Protective Devices SPD Class II → Type T2 40kA

