

## Timing relay, star-delta, 50 ms, 1W, 3-60s, 24-240VAC/DC



Powering Business Worldwide™

Part no.	ETR4-51-A
Catalog No.	031884
Alternate Catalog No.	XTTR6A60S51B
EL-Nummer	4133308
(Norway)	

## Delivery program

Product range	ETR4 timing relays		
Basic function	Timer relays		
Function	Star-delta switching		
	Changeover contact with a changeover time of 50 ms		
Number of changeover contacts	Fixed timing function		
Time range	1		
Time range	3 - 60 s		
<b>Rated operational current</b>			
AC-14			
300 V	$I_e$	A	3
380 V 400 V 415 V	$I_e$	A	3
	Value applies starting with release 001.		
AC-15			
220 V 230 V 240 V	$I_e$	A	3
300 V	$I_e$	A	3
380 V 400 V 415 V	$I_e$	A	3
	Value applies starting with release 001.		
Voltage range	$U_{LN}$	V	24 - 240 V AC, 50/60 Hz 24 - 240 V DC
Width		mm	22.5

## Technical data

General			
Standards			Standard IEC/EN 61812 VDE 0435
Lifespan, mechanical			
AC operated	Operations	$\times 10^6$	30
DC operated	Operations	$\times 10^6$	30
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Ambient temperature			
Ambient temperature, storage		°C	- 45 - + 85
Open		°C	- 25 - + 60
Enclosed		°C	- 25 - + 45
Mounting position			As required
Mechanical shock resistance (IEC/EN 60068-2-27)			
Half-sinusoidal shock, 20 ms		g	
Make contact		g	4
Degree of protection			
Terminals			IP20
Weight		kg	0.1
Terminal capacities		mm <sup>2</sup>	
Solid		mm <sup>2</sup>	1 x (0.5 - 2.5) 2 x (0.5 - 1.5)
Flexible with ferrule		mm <sup>2</sup>	1 x (0.5 - 2.5) 2 x (0.5 - 1.5)

Solid or stranded	AWG	1 x (20 - 14)
<b>Contacts</b>		
Rated impulse withstand voltage	$U_{imp}$	V AC 4000
Rated impulse withstand voltage	$U_{imp}$	V AC 6000
		Value applies starting with release 001.
Overvoltage category/pollution degree		III/2
Rated insulation voltage	$U_i$	V AC 400
Rated insulation voltage	$U_i$	V AC 600
		Value applies starting with release 001.
Rated operational voltage	$U_e$	V AC 300
Rated operational voltage	$U_e$	V AC 440
		Value applies starting with release 001.
Safe isolation to EN 61140		
between coil and auxiliary contacts		V AC 250
between the auxiliary contacts		V AC 250
Making capacity		
AC-14 $\cos \varphi = 0.3$ 400 V		A 48
AC-15 $\cos \varphi = 0.3$ 220 V		A 50
DC-11 L/R - 40 ms		$\times I_e$ 1.1
Breaking capacity		
AC-14 $\cos \varphi = 0.3$ 440 V		A 3
AC-15 $\cos \varphi = 0.3$ 220 V		A 3
DC-11 L/R - 40 ms		$\times I_e$ 1.1
Rated operational current	$I_e$	A
AC-14	$I_e$	
380 V 400 V 415 V	$I_e$	A 3
		Value applies starting with release 001.
AC-14		
440 V	$I_e$	A 3
AC-15		
220 V 230 V 240 V	$I_e$	A 3
DC-11		
Note		Making and breaking conditions to DC13, time constant as stated
L/R max. 15 ms		A
24 V	$I_e$	A 1.5
L/R max. 50 ms		A 1.2
Conv. thermal current	$I_{th}$	A 6
Short-circuit rating without welding		
Note		When supplied directly from mains or transformer > 1000 VA
Max. fuse, make contacts		A gG/gL 6
Max. fuse, break contacts		A gG/gL 6
Max. overcurrent protective device, 220/230 V	Type	FAZ-B4/1-HI

## Magnet systems

Power consumption		
Pick-up AC	VA	2
Sealing AC	VA	2
Pick-up DC	W	1.8
Sealing DC	W	1.8
Duty factor	% DF	100
Maximum operating frequency	Ops/h	4000
Minimum command time		
AC	ms	50
DC	ms	30
Repetition accuracy (deviation)	%	$\leq 0.5$
Recovery time (after 100% time delay)	ms	70

Contact changeover time	$t_u$	ms	50
<b>Electromagnetic compatibility (EMC)</b>			
Electrostatic discharge (ESD)			
applied standard			IEC/EN 61000-4-2
Air discharge		kV	8
Contact discharge		kV	6
Electromagnetic fields (RFI)			
applied standard			IEC/EN 61000-4-3
		V/m	80 - 1000 MHz: 10 1.4 - 2 GHz: 3 2.0 - 2.7 GHz: 1
Radio interference suppression			EN 55011, Class B (conducted) EN 55011, Class B (radiated)
Burst		kV	Supply cables: 2 Signal cables: 1 according to IEC/EN 61000-4-4
power pulses (Surge)			2 kV (symmetrical) 4 kV (asymmetrical) according to IEC/EN 61000-4-5
Immunity to line-conducted interference to (IEC/EN 61000-4-6)		V	10

## Design verification as per IEC/EN 61439

Technical data for design verification	$I_n$	A	6
Rated operational current for specified heat dissipation	$P_{vid}$	W	1.4
Heat dissipation per pole, current-dependent	$P_{vid}$	W	0
Equipment heat dissipation, current-dependent	$P_{vs}$	W	1.8
Static heat dissipation, non-current-dependent	$P_{diss}$	W	0
Heat dissipation capacity		°C	-25
Operating ambient temperature min.		°C	60
Operating ambient temperature max.			
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 8.0

Relays (EG000019) / Timer relay (EC001439)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Relay and socket / Timed relay (ecl@ss10.0.1-27-37-16-05 [AKF092013])

Type of electric connection		Screw connection
Function delay-on energization		No
Function delay on de-energization		No
Function floating contact on energization		No
Function floating contact on de-energization		No
Function star-delta		Yes
Function pulse shaping		No
Function flashing, starting with pause, fixed time		No
Function flashing, starting with pulse, fixed time		No
Clock function, starting with pause, variable		No
Clock function, starting with pulse, variable		No
With plug-in socket		No
Remote operation possible		No
Suitable as remote control		No
Pluggable on auxiliary contact block		No
Rated control supply voltage Us at AC 50HZ	V	24 - 240
Rated control supply voltage Us at AC 60HZ	V	24 - 240
Rated control supply voltage Us at DC	V	24 - 240
Voltage type for actuating		AC/DC
Nominal current	A	3
Time range	s	3 - 60
Number of outputs, undelayed, normally closed contact		0
Number of outputs, undelayed, normally open contact		1
Number of outputs, undelayed, change-over contact		0
Number of outputs, delayed, normally closed contact		0
Number of outputs, delayed, normally open contact		1
Number of outputs, delayed, change-over contact		0
Outputs, reversible delayed/undelayed		No
With semiconductor output		No
Suitable for DIN rail (top hat rail) mounting		Yes
Suitable for front mounting		No
Width	mm	23
Height	mm	83
Depth	mm	103