



Timing relay, electronic with star-delta (wye-delta) function 1 NO delayed 1 NO instantaneous 1 time range, 3...60 s 12-240 V AC/DC at 50/60 Hz AC with LED, Screw terminal

product brand name	SIRIUS
product designation	timing relay
design of the product	Star-delta (wye-delta) function
product type designation	3RP25
General technical data	
product component	
• relay output	Yes
• semi-conductor output	No
product extension required remote control	No
product extension optional remote control	No
power loss [W] maximum	2 W
insulation voltage for overvoltage category III according to IEC 60664 with degree of pollution 3 rated value	300 V
test voltage for isolation test	2.5 kV
degree of pollution	3
surge voltage resistance rated value	4 000 V
protection class IP	IP20
shock resistance according to IEC 60068-2-27	11g / 15 ms
mechanical service life (operating cycles) typical	10 000 000
electrical endurance (operating cycles) at AC-15 at 230 V typical	100 000
adjustable time	3 ... 60 s
relative setting accuracy relating to full-scale value	5 %; +/-
thermal current	5 A
recovery time	250 ms
reference code according to IEC 81346-2	K
relative repeat accuracy	1 %; +/-
influence of the surrounding temperature	1% in the whole temperature range to the set runtime
power supply influence	1% in the whole voltage range to the set runtime
Substance Prohibitance (Date)	09/12/2014
SVHC substance name	Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one - 71868-10-5
Control circuit/ Control	
type of voltage of the control supply voltage	AC/DC
control supply voltage 1 at AC	
• at 50 Hz	12 ... 240 V
• at 60 Hz	12 ... 240 V
control supply voltage frequency 1	50 ... 60 Hz
control supply voltage 1 at DC	
•	12 ... 240 V

operating range factor control supply voltage rated value at DC - initial value - full-scale value	0.8 1.1
operating range factor control supply voltage rated value at AC at 50 Hz - initial value - full-scale value	0.8 1.1
operating range factor control supply voltage rated value at AC at 60 Hz - initial value - full-scale value	0.8 1.1
inrush current peak - at 24 V - at 240 V	0.5 A 5 A
duration of inrush current peak - at 24 V - at 240 V	0.4 ms 0.5 ms
Switching Function	
switching function - ON-delay - ON-delay/instantaneous contact - passing make contact - passing make contact/instantaneous contact - OFF delay	No No No No No
switching function - flashing symmetrically with interval start/instantaneous - flashing symmetrically with interval start - flashing symmetrically with pulse start/instantaneous - flashing symmetrically with pulse start - flashing asymmetrically with interval start - flashing asymmetrically with pulse start	No No No No No No
switching function - star-delta circuit with delay time - star-delta circuit	No Yes
switching function with control signal - additive ON-delay - passing break contact - passing break contact/instantaneous - OFF delay - OFF delay/instantaneous - pulse delayed - pulse delayed/instantaneous - pulse-shaping - pulse-shaping/instantaneous - additive ON-delay/instantaneous - ON-delay/OFF-delay/instantaneous - passing make contact - passing make contact/instantaneous contact	No No No No No No No No No No No No No No
switching function of interval relay with control signal - retrotriggerable with deactivated control signal/instantaneous contact - retrotriggerable with switched-on control signal - retrotriggerable with switched-on control signal/instantaneous contact - retriggerable with deactivated control signal	No No No No
Short-circuit protection	
design of the fuse link for short-circuit protection of the auxiliary switch required	fuse gL/gG: 4 A
Auxiliary circuit	
material of switching contacts	AgSnO2
number of NC contacts	

• delayed switching • instantaneous contact	0
number of NO contacts	0
• delayed switching • instantaneous contact	1
number of CO contacts	1
• delayed switching • instantaneous contact	0
operational current of auxiliary contacts at AC-15	0
• at 24 V • at 250 V	3 A
operational current of auxiliary contacts at DC-13	3 A
• at 24 V • at 125 V • at 250 V	1 A
operating frequency with 3RT2 contactor maximum	0.2 A
contact reliability of auxiliary contacts	0.1 A
contact rating of auxiliary contacts according to UL	5 000 1/h
switching capacity current with inductive load	one incorrect switching operation of 100 million switching operations (17 V, 5 mA)
Inputs/ Outputs	
product function	
• at the relay outputs switchover delayed/without delay • non-volatile	No
Electromagnetic compatibility	
EMC emitted interference according to IEC 61812-1	ambience A (industrial sector)
EMC immunity according to IEC 61812-1	corresponds to degree of severity 3
conducted interference	
• due to burst according to IEC 61000-4-4 • due to conductor-earth surge according to IEC 61000-4-5 • due to conductor-conductor surge according to IEC 61000-4-5	2 kV network connection / 1 kV control connection
field-based interference according to IEC 61000-4-3	2 kV
electrostatic discharge according to IEC 61000-4-2	1 kV
Safety related data	
category according to EN 954-1	10 V/m
Electrical Safety	
protection class IP on the front according to IEC 60529	4 kV contact discharge / 8 kV air discharge
type of insulation	
Connections/ Terminals	
product component removable terminal for auxiliary and control circuit	Yes
type of electrical connection for auxiliary and control circuit	screw-type terminals
type of connectable conductor cross-sections	
• solid • finely stranded with core end processing • for AWG cables solid • for AWG cables stranded	1x (0.5 ... 4.0 mm²), 2x (0.5 ... 2.5 mm²)
connectable conductor cross-section	1x (0.5 ... 4 mm²), 2x (0.5 ... 1.5 mm²)
• solid • finely stranded with core end processing	1x (20 ... 12), 2x (20 ... 14)
AWG number as coded connectable conductor cross section	1x (20 ... 12), 2x (20 ... 14)
• solid • stranded	0.5 ... 4 mm²
tightening torque	0.5 ... 4 mm²
design of the thread of the connection screw	20 ... 12
Installation/ mounting/ dimensions	
mounting position	20 ... 14
fastening method	0.6 ... 0.8 N·m
height	M3
width	

depth	90 mm
required spacing	
• with side-by-side mounting	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm
• for grounded parts	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— at the side	0 mm
— downwards	0 mm
• for live parts	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm

Ambient conditions

installation altitude at height above sea level maximum	2 000 m
ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
relative humidity during operation	10 ... 95 %

Approvals Certificates

General Product Approval



[Confirmation](#)



EMV	Test Certificates	Marine / Shipping
-----	-------------------	-------------------



[KC](#)

[Type Test Certificates/Test Report](#)



Marine / Shipping	other	Environment
-------------------	-------	-------------



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RP2576-1NW30>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RP2576-1NW30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RP2576-1NW30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RP2576-1NW30&lang=en

Characteristic: Derating



