Fuse-link, high speed, 5 A, DC 1500 V, IEC 60269-6 type A, 10 x 85 mm, gPV, UL PV, UL, IEC



PV-5A10F85L

General specifications	
Product name	Eaton Bussmann series photovoltaic fuses
Part no.	PV-5A10F85L
EAN	5027590506335
Product Length/Depth	85 millimetre
Product height	10 millimetre
Product width	10 millimetre
Product weight	18.6 gram
Compliances	RoHS Compliant CE Marked
Certifications	UL Listed IEC 60269 CSA Certified
Product Tradename	None
Product Type	High speed photovoltaic fuse
Product Sub Type	None
Electrical data	
Amperage Rating	5 A
Voltage rating	1500 Vdc
Interrupt rating	30 kAIC
Class	Class gPV
Product specifications	
Application	Photovoltaic systems, inverters ,Photovoltaic strings
Fuse type	PV-A10F85L
Fuse indicator	Non Indicating
Fuse size	10 x 85 mm
Compatible fuse holders	
Suitable for	CHPV15L85 Fuse holder

Technical data ETIM 9.0

Technical data Ethii 3.0				
Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)				
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])				
Model		Fiberglass fuse		
Size		Other		
Voltage type		DC		
Rated current	Α	5		
Rated voltage	V	1500		
Utilization category		gPV (photovoltaic protection)		
Rated operating frequency	Hz			
Type of fuse status indicator		Other		
Release characteristic		Other		
Breaking capacity	kA	30		
Power loss at rated current	W	2.8		