



SCALANCE XB004-1G unmanaged Industrial Ethernet Switch for 10/100/1000 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V DC power supply, with 4x 10/100/1000 Mbit/s RJ45 ports electrical and 1 x 1000 Mbit/s SC-port optical (multimode, glass), up to max. 750 m Manual available as a download .

<b>product type designation</b>		SCALANCE XB004-1G
<b>transfer rate</b>		
transfer rate		10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
<b>interfaces / for communication / maximum configuration for modular devices</b>		
number of electrical ports / maximum	4	
number of optical ports / maximum	1	
<b>interfaces / for communication / integrated</b>		
number of electrical connections		
• for network components or terminal equipment	4; RJ45	
number of 100 Mbit/s SC ports		
• for multimode	0	
number of 1000 Mbit/s SC ports		
• for multimode	1	
<b>interfaces / other</b>		
number of electrical connections		
• for power supply	1	
type of electrical connection		
• for power supply	3-pole terminal block	
<b>supply voltage, current consumption, power loss</b>		
<b>type of voltage / 1 / of the supply voltage</b>		DC
• supply voltage / 1 / rated value	24 V	
• power loss [W] / 1 / rated value	12.5 W	
• supply voltage / 1 / rated value	19.2 ... 28.8 V	
• consumed current / 1 / maximum	0.52 A	
• type of electrical connection / 1 / for power supply	3-pole terminal block	
• product component / 1 / fusing at power supply input	Yes	
• fuse protection type / 1 / at input for supply voltage	0.6 A / 60 V	
<b>ambient conditions</b>		
ambient temperature		
• during operation	-10 ... +60 °C	
• during storage	-40 ... +80 °C	
• during transport	-40 ... +80 °C	
relative humidity		
• at 25 °C / without condensation / during operation / maximum	95 %	
protection class IP	IP20	
<b>design, dimensions and weights</b>		
design	Box	
width	45 mm	
height	100 mm	

depth	87 mm
net weight	0.21 kg
fastening method	
• 35 mm top hat DIN rail mounting	Yes
• wall mounting	Yes
• S7-1500 rail mounting	No
<b>product functions / management, configuration, engineering</b>	
product function	
• multiport mirroring	No
• CoS	Yes
PROFINET conformity class	A
product function / switch-managed	No
<b>product functions / redundancy</b>	
product function	
• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
<b>standards, specifications, approvals</b>	
standard	
• for FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
MTBF	124 a
reference code	
• according to IEC 81346-2	KF
• according to IEC 81346-2:2019	KFE
<b>standards, specifications, approvals / CE</b>	
certificate of suitability / CE marking	Yes
<b>standards, specifications, approvals / hazardous environments</b>	
standard / for hazardous zone	
•	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
certificate of suitability	
• CCC / for hazardous zone according to GB standard	Yes; GB3836.1, GB3836.8
• CCC / for hazardous zone according to GB standard / as marking	Ex nA IIC T4 Gc
<b>standards, specifications, approvals / other</b>	
certificate of suitability	
• C-Tick	EN 61000-6-2, EN 61000-6-4
• KC approval	Yes
•	Yes
<b>standards, specifications, approvals / Environmental Product Declaration</b>	
Environmental Product Declaration	Yes
Global Warming Potential [CO2 eq]	
• total	141.3 kg
• during manufacturing	15.99 kg
• during operation	125.18 kg
• after end of life	0.15 kg
<b>product functions / general</b>	
Warranty period	5 a
<b>further information / internet links</b>	
internet link	
• to website: Image database	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial security concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such

systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial security measures that may be implemented, please visit <https://www.siemens.com/industrialsecurity>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Security RSS Feed under <https://www.siemens.com/cert>. (V4.6)

## Approvals / Certificates

### General Product Approval



[Declaration of Conformity](#)



EMV

For use in hazardous locations

Environment

KC



IECEx



ATEX

FM

CCC-Ex



### Industrial Communication

[PROFINET](#)

last modified:

2/9/2024