



Figure similar

SIMATIC ET 200SP, PROFINET bundle IM, IM 155-6PN ST, max. 32 I/O modules and 16 ET 200AL modules, single hot swap, bundle consists of: Interface module (6ES7155-6AU01-0BN0), Server module (6ES7193-6PA00-0AA0), BusAdapter BA 2xRJ45 (6ES7193-6AR00-0AA0)

General information	
Product type designation	IM155-6PN ST, including BusAdapter BA 2x RJ45
HW functional status	From FS03
Product function	
<ul style="list-style-type: none"> <li>• I&amp;M data</li> <li>• Module swapping during operation (hot swapping)</li> <li>• Isochronous mode</li> </ul>	<p>Yes; I&amp;M0 to I&amp;M3 Yes; Single hot swapping No</p>
Engineering with	
<ul style="list-style-type: none"> <li>• STEP 7 TIA Portal configurable/integrated from version</li> <li>• STEP 7 configurable/integrated from version</li> <li>• PROFINET from GSD version/GSD revision</li> </ul>	<p>V14 V5.5 SP4 and higher V2.3 / -</p>
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
<ul style="list-style-type: none"> <li>• Mains/voltage failure stored energy time</li> </ul>	10 ms
Input current	
Current consumption (rated value)	450 mA
Current consumption, max.	550 mA
Inrush current, max.	3.7 A
$I^2t$	0.09 A <sup>2</sup> ·s
Power	
Infeed power to the backplane bus	4.5 W
Power loss	
Power loss, typ.	1.9 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>• Address space per module, max.</li> </ul>	256 byte; per input / output
Address space per station	
<ul style="list-style-type: none"> <li>• Address space per station, max.</li> </ul>	512 byte; Dependent on configuration
Hardware configuration	
Rack	
<ul style="list-style-type: none"> <li>• Modules per rack, max.</li> </ul>	32; + 16 ET 200AL modules

<b>Submodules</b>	
• Number of submodules per station, max.	256
<b>Interfaces</b>	
Number of PROFINET interfaces	1; 2 ports (switch)
<b>1. Interface</b>	
<b>Interface types</b>	
• Number of ports	2
• integrated switch	Yes
• BusAdapter (PROFINET)	Yes; compatible BusAdapters: BA 2x RJ45, BA 2x FC, BA 2x M12
<b>Protocols</b>	
• PROFINET IO Device	Yes
• Open IE communication	Yes
• Media redundancy	Yes; PROFINET MRP
<b>PROFINET IO Device</b>	
<b>Services</b>	
— IRT	Yes; with send cycles of between 250 µs and 4 ms in increments of 125 µs
— PROFIenergy	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2
<b>Interface types</b>	
<b>RJ 45 (Ethernet)</b>	
• Transmission procedure	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
• 10 Mbps	Yes; for Ethernet services
• 100 Mbps	Yes; PROFINET with 100 Mbit/s full duplex (100BASE-TX)
• Autonegotiation	Yes
• Autocrossing	Yes
<b>Protocols</b>	
<b>PROFINET IO Device</b>	
<b>Services</b>	
— IRT	Yes; with send cycles of between 250 µs and 4 ms in increments of 125 µs
— PROFIenergy	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2
<b>Redundancy mode</b>	
• PROFINET system redundancy (S2)	No
<b>Media redundancy</b>	
— MRP	Yes
— MRPD	No
<b>Open IE communication</b>	
• TCP/IP	Yes
• SNMP	Yes
• LLDP	Yes
<b>Interrupts/diagnostics/status information</b>	
Status indicator	Yes
Alarms	Yes
Diagnostics function	Yes
<b>Diagnostics indication LED</b>	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
<b>Potential separation</b>	
between backplane bus and electronics	No
between PROFINET and all other circuits	Yes; 1500 V AC (type test)
between supply and all other circuits	No
<b>Permissible potential difference</b>	
between different circuits	Safety extra low voltage SELV

<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Standards, approvals, certificates</b>	
Network loading class	2
Security level	According to Security Level 1 Test Cases V1.1.1
<b>Ambient conditions</b>	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	50 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
<b>connection method / header</b>	
ET-Connection	
• via BU/BA Send	Yes; + 16 ET 200AL modules
<b>Dimensions</b>	
Width	50 mm
Height	117 mm
Depth	74 mm
<b>Weights</b>	
Weight, approx.	147 g; without BusAdapter

**last modified:** 3/31/2023 