



Connection, on rear, 3p, 1 page, size 4

Part no. **NZM4-XKR**
266842
EL Number **4359062**
(Norway)

General specifications

Product name	Eaton Moeller series NZM connection type
Part no.	NZM4-XKR
EAN	4015082668426
Product Length/Depth	45 millimetre
Product height	63 millimetre
Product width	135 millimetre
Product weight	1.667 kilogram
Compliances	RoHS conform IEC
Product Tradename	NZM
Product Type	Accessories
Product Sub Type	Connection type

Delivery program

Type	Accessory Connection on rear Terminal
Number of poles	Three-pole
Amperage Rating	≤ 1250 A
Frame	NZM4
Suitable for	Aluminum cable lug Copper cable lugs Three-pole
Used with	NZM4, N4

Technical Data - Mechanical - Terminals

Terminal capacity (stranded cable)	70 mm ² - 185 mm ² (2x) 120 mm ² - 185 mm ² (1x) 35 mm ² - 185 mm ² (4x) 95 mm ² - 185 mm ² (2x) 50 mm ² - 185 mm ² (4x) 185 mm ² (1x)
Terminal capacity (copper busbar)	50 mm x 10 mm (2x)
Terminal capacity (copper strip)	10 segments of 50 mm x 1 mm (2x)

Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information		
Model		Other

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Wiring set for power circuit breaker (EC002050)	
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Wiring set for circuit breaker (ecl@ss13-27-37-04-24 [ACN957016])	
Suitable for number of poles	3
Model	Other