

## Top-hat rail 35x15mm

Part no. **TS35X15**  
 Catalog No. **050657**

## Delivery program

|               |  |  |   |
|---------------|--|--|---|
| Product range |  |  | General switchboard accessories   |
| Accessories   |  |  | DIN-rail  |
| Standards     |  |  | according to IEC/EN 60715   |
| Description   |  |  | 35 x 15 mm. Short-circuit strength as PE conductor corresponds to 50 mm <sup>2</sup> copper conductor as defined in IEC/EN 61439-1. Supplied in lengths of 2 m. |

## Dimensions

|        |  |    |      |
|--------|--|----|------|
| Width  |  | mm | 35   |
| Height |  | mm | 15   |
| Length |  | mm | 2000 |

## Technical data ETIM 8.0

|  |  |    |                                   |
|--|--|----|-----------------------------------|
| Energy distribution systems (EG000015) / Mounting rail (EC001285)  |  |    |                                   |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / DIN rail (ecl@ss10.0.1-27-40-06-02 [ACO367011]) |  |    |                                   |
| Model  |  |    | DIN rail (top hat rail) 35/15 mm  |
| Material   |  |    | Steel                             |
| Surface protection   |  |    | Galvanic/electrolytic zinc plated |
| Punch shape  |  |    | None                              |
| Drill hole distance centrally  |  | mm | 0                                 |
| Material thickness   |  | mm | 1                                 |
| Length   |  | mm | 35                                |
| Height   |  | mm | 15                                |