

Series connection digital time switch 1 channel, 7 days, text line, 1 TLE



Powering Business Worldwide™

Part no.	TSDW1COMIN
Catalog No.	167383
Alternate Catalog No.	TSDW1COMIN
EL-Nummer	1456985
(Norway)	

Technical data

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	0
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	0
Static heat dissipation, non-current-dependent	P_{vs}	W	0.4
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
			0

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Digital time switch for distribution board (EC002305)

Electric engineering, automation, process control engineering / Measurement technology, process measurement technology / Measuring appliance, time / Digital time switch (ecl@ss10.0.1-27-20-01-10 [ACN653011])

Mounting method		DIN rail
Number of channels		1
Supply voltage	V	230 - 240
Voltage type of supply voltage		AC
Frequency supply voltage	Hz	50 - 60
Autonomy in hours		0
Autonomy in years		10
Accuracy per day	s	1
Text guidance in display		Yes
External programming		Yes
With memory card		No
60 min program		Yes
24 h program		Yes
Weekly program		Yes
Annual program		No
Holiday program		Yes
Impulse program		No
Cycle program		No
Astro program		No
Random program		No
Hour meter		Yes
Mains synchronous		No
Quartz controlled		Yes
Radio-controlled		No
Radio-controlled (DCF77)		No
GPS (global positioning system)		No
Contact type		Change-over contact (NO/NC)
Number of contacts		1
Shortest switching time channel 1	min	1

Shortest switching time channel 2	min	0
Number of memory locations		84
Automatic switching summer-/winter time		Yes
Suitable for manual operation		Yes
External pushbutton input		No
Switching preselection		Yes
Nominal switching current at 250 V AC	A	16
Max. switching power LED	W	600
Potential free switch contact		Yes
Degree of protection (IP)		IP20
Width in number of modular spacings		1
Width	mm	17.5
Height	mm	90
Depth	mm	65.5