

wkładki bezpiecznikowe cylindryczne

przemysłowe typu gG i aM



Pak.	Nr ref.		Cylindryczne typ gG		
	Bez sygnaliz.	Z sygnal.	Zgodne z normami EN/IEC 60269-1, EN/IEC 60269-2		
			Prąd znamion. [A]	Napięcie [V~]	Zdolność łączeniowa [A]
			8 x 32		
10	0123 01		1		
10	0123 02	0124 02	2		
10	0123 04	0124 04	4		
10	0123 06	0124 06	6		
10	0123 08		8	400	20 000
10	0123 10		10		
10		0124 10	10		
10	0123 12		12		
10	0123 16	0124 16	16		
			Zgodne z normami EN 60269-1 i -2, IEC 60269-1, -2 i -2-1 NF C 63-213 (07. 1995). Akceptacje Bureau Veritas HRC (Haut Pouvoir de Coupure)		
			10 x 38		
10	0133 94		0,5		
10	0133 01		1		
10	0133 02	0134 02	2		
10	0133 04	0134 04	4		
10	0133 06	0134 06	6	500	100 000
10	0133 08	0134 08	8		
10	0133 10	0134 10	10		
10	0133 12		12		
10	0133 16	0134 16	16		
10	0133 20	0134 20	20		
10	0133 25	0134 25	25		
	Bez wybijaka	Z wybijakiem	14 x 51		
10	0143 02		2		
10	0143 04		4		
10	0143 06	0145 06	6		
10	0143 10	0145 10	10		
10	0143 16	0145 16	16	500	100 000
10	0143 20	0145 20	20		
10	0143 25	0145 25	25		
10	0143 32	0145 32	32		
10	0143 40	0145 40	40		
10	0143 50 ⁽¹⁾	0145 50	50		
			22 x 58		
10	0153 10		10		
10	0153 16		16		
10	0153 20		20		
10	0153 25		25	500	100 000
10	0153 32	0155 32	32		
10	0153 40	0155 40	40		
10	0153 50	0155 50	50		
10	0153 63	0155 63	63		
10	0153 80	0155 80	80		
10	0153 96	0155 96	100		
10	0153 97 ⁽¹⁾	0155 97 ⁽¹⁾	125	400	

Pak.	Nr ref.		Cylindryczne typ aM		
	Bez sygnaliz.	Z sygnal.	Zgodne z normami EN/IEC 60269-1, EN/IEC 60269-2		
			Prąd znamion. [A]	Napięcie [V~]	Zdolność łączeniowa [A]
			8 x 32		
10	0120 01		1		
10	0120 02		2		
10	0120 04		4	400	20 000
10	0120 06		6		
10	0120 08		8		
10	0120 10		10		
			Zgodne z normami EN 60269-1 i -2, IEC 60269-1, -2 i -2-1 NF C 63-213 (07. 1995). Akceptacje Bureau Veritas HRC (Haut Pouvoir de Coupure)		
			10 x 38		
10	0130 92		0,25		
10	0130 95		0,50		
10	0130 01		1		
10	0130 02		2		
10	0130 04		4		
10	0130 06		6		
10	0130 08		8	500	100 000
10	0130 10		10		
10	0130 12		12		
10	0130 16		16		
10	0130 20 ⁽²⁾		20	400	
10	0130 25 ⁽²⁾		25	400	
			14 x 51		
10	0140 04		4		
10	0140 06		6		
10	0140 08		8		
10	0140 10		10		
10	0140 12		12	500	100 000
10	0140 16		16		
10	0140 20		20		
10	0140 25	0141 25	25		
10	0140 32	0141 32	32		
10	0140 40	0141 40	40		
10	0140 50 ⁽¹⁾	0141 50 ⁽¹⁾	50	400	
			22 x 58		
10	0150 25		25		
10	0150 32		32	500	100 000
10	0150 40		40		
10	0150 50	0151 50	50		
10	0150 63	0151 63	63		
10	0150 80	0151 80	80		
10	0150 96		100		
10	0150 97 ⁽¹⁾		125	400	
			Wkładki – zwory metalowe		
10	0133 00		10 x 38		
10	0143 00		14 x 51		
10	0153 00		22 x 58		

⁽¹⁾ Zakresy nadprądowe normalizowane.
⁽²⁾ Zakresy nadprądowe nienormalizowane.