

wkładki bezpiecznikowe cylindryczne miniaturowe



0102 63

wkładki bezpiecznikowe cylindryczne standardowe



0113 06



0113 10



0124 20



0126 25



0134 32

Pak.	Nr ref.	Wkładki cylindryczne miniaturowe 5 x 20		
		Ceramiczne, szybkiego zadziałania. Zgodne z normą EN/IEC 60127-2. Wysoka zdolność zwarciovą.		
		Prąd znamionowy (A)	Napięcie (V)	Zdolność zwarciovą (A)
10	0102 02	0,2	250	1 500
10	0102 05	0,5		1 500
10	0102 06	0,63		1 500
10	0102 10	1		1 500
10	0102 12	1,25		1 500
10	0102 16	1,6		1 500
10	0102 20	2		1 500
10	0102 25	2,5		1 500
10	0102 30	3,15		1 500
10	0102 50	5		1 500
10	0102 63	6,3		1 500
10	0102 96	10		500

Pak.	Nr ref.	Wkładki cylindryczne standardowe				
		8,5 x 23 bez sygnalizacji				
		Prąd znamionowy (A)	Napięcie (V)	Zdolność zwarciova (A)	Przekrój chronionego przewodu (mm²)	Identyfikacja kolorem
10	0113 02	2	230	6000	1,5	
10	0113 04	4				
10	0113 06	6				
10	0113 10	10				
		10,3 x 25,8 bez sygnalizacji				
10	0116 06	4	230	6000	2,5	
10	0116 10	6				
10	0116 16	10				
		8,5 x 31,5 bez sygnalizacji				
10	0123 94	0,5	400	20000	2,5	
10	0123 01	1				
10	0123 02	2				
10	0123 04	4				
10	0123 06	6				
10	0123 08	8				
10	0123 10	10				
10	0123 12	12				
10	0123 16	16				
10	0123 20	20				
		8,5 x 31,5 z sygnalizacją				
10	0124 02	2	400	20000	2,5	
10	0124 04	4				
10	0124 06	6				
10	0124 10	10				
10	0124 16	16				
10	0124 20	20				
		10,3 x 31,5 bez sygnalizacji				
10	0126 20	20	400	20000	4	
10	0126 25	25				
		10,3 x 31,5 z sygnalizacją				
10	0127 25	38	400	20000	4	
		10,3 x 38 bez sygnalizacji				
10	0133 32	38	400	20000	6	
		10,3 x 38 z sygnalizacją				
10	0134 32	32	400	20000	6	
		Wkładka zwierająca N				
10	0133 00	10 x 38				

