

Fuse-link with blink application, D01, 10A, 24 V, gL/gG, set consists of 3 pcs.

Part no. Z-SLS/B/24-10A  
Catalog No. 268998

Similar to illustration

## Delivery program

Product range			Fuse material
Basic function			Accessories
Basic function			Fuse sets
For use with			Z-SLS/NEQZ Z-SLK/NEQZ Z-SLS/CEK
			With flashing function Snap-fit on DIN rail 1 set consists of: 3 fuse-links, 3 current codings, 1 plastic box in the colour of the indicator
Rated operating voltage			24 - 60 V AC/DC
Rated uninterrupted current	$I_u$	A	10

## Technical data

### Electrical

Rated operational voltage	$U_e$	V	
Rated operating voltage	$U_e$	V AC	24 - 60
		V DC	24 - 60
Utilization category			gL (gL)
Test voltage		kV	5

## Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	10
Heat dissipation per pole, current-dependent	$P_{vid}$	W	0
Equipment heat dissipation, current-dependent	$P_{vid}$	W	1.1
Static heat dissipation, non-current-dependent	$P_{vs}$	W	0
Heat dissipation capacity	$P_{diss}$	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
			0

## Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss10.0.1-27-14-21-19 [ACN353011])			
Construction size			D01
Rated current		A	10
Rated voltage		V	24
Colour code			Red
Utilization category			gL/gG (cable protection/equipment protection)