

Fuse-link with blink application, D02, 63A, 24 V, gL/gG, set consists of 3 pcs.

Part no. Z-SLS/B/24-63A
Catalog No. 269004

Similar to illustration

Delivery program

Product range			Fuse material
Basic function			Accessories
Basic function			Fuse sets
For use with			Z-SLS/NE0Z Z-SLK/NE0Z Z-SLS/CEK
			With flashing function Snap-fit on DIN rail 1 set consists of: 3 fuse-links, 3 current codings, 1 plastic box in the colour of the indicator
Rated operating voltage			24 - 60 V AC/DC
Rated uninterrupted current	I_u	A	63

Technical data

Electrical

Rated operational voltage	U_e	V	
Rated operating voltage	U_e	V AC	24 - 60
		V DC	24 - 60
Utilization category			gL (gL)
Test voltage		kV	5

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	63
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	5
Static heat dissipation, non-current-dependent	P_{vs}	W	0
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
			0

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss10.0.1-27-14-21-19 [ACN353011])			
Construction size			D02
Rated current		A	63
Rated voltage		V	24
Colour code			Copper
Utilization category			gL/gG (cable protection/equipment protection)