



circuit breaker 3VA1 IEC frame 630 breaking capacity class S  $I_{cu}=36\text{kA}$  @ 415V 3-pole, line protection TM240, ATAM,  $I_n=630\text{A}$  overload protection  $I_r=440\text{A}\dots630\text{A}$  short-circuit protection  $I_i=4\dots8 \times I_n$  nut keeper kit

| Model                                                                                                 |                             |
|-------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                    | SENTRON                     |
| product designation                                                                                   | Molded case circuit breaker |
| design of the product                                                                                 | Line protection             |
| design of the overcurrent release                                                                     | TM240                       |
| protection function of the overcurrent release                                                        | LI                          |
| number of poles                                                                                       | 3                           |
| General technical data                                                                                |                             |
| insulation voltage / rated value                                                                      | 800 V                       |
| operating voltage / at DC / rated value                                                               | 500 V                       |
| operating voltage / at AC / rated value                                                               | 690 V                       |
| power loss [W] / maximum                                                                              | 192.9 W                     |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole           | 64.3 W                      |
| mechanical service life (operating cycles) / typical                                                  | 20 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                      | 4 000                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                          | 3 000                       |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof | No                          |
| ground-fault monitoring version                                                                       | Without                     |
| product function                                                                                      |                             |
| • communication function                                                                              | No                          |
| • other measurement function                                                                          | No                          |
| Net Weight                                                                                            | 4.951 kg                    |
| Current                                                                                               |                             |
| operational current                                                                                   |                             |
| • at 40 °C                                                                                            | 630 A                       |
| • at 45 °C                                                                                            | 630 A                       |
| • at 50 °C                                                                                            | 630 A                       |
| • at 55 °C                                                                                            | 618 A                       |
| • at 60 °C                                                                                            | 607 A                       |
| • at 65 °C                                                                                            | 595 A                       |
| • at 70 °C                                                                                            | 583 A                       |
| Switching capacity according to IEC 60947                                                             |                             |
| switching capacity class of the circuit breaker                                                       | S                           |
| maximum short-circuit current breaking capacity ( $I_{cu}$ )                                          |                             |
| • at 240 V                                                                                            | 55 kA                       |
| • at 415 V                                                                                            | 36 kA                       |
| • at 440 V                                                                                            | 36 kA                       |
| • at 500 V                                                                                            | 25 kA                       |
| • at 690 V                                                                                            | 7 kA                        |

|                                                                                           |                                                                                                                                                                |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| operating short-circuit current breaking capacity (Ics)                                   |                                                                                                                                                                |
| • at 240 V                                                                                | 55 kA                                                                                                                                                          |
| • at 415 V                                                                                | 36 kA                                                                                                                                                          |
| • at 440 V                                                                                | 25 kA                                                                                                                                                          |
| • at 500 V                                                                                | 25 kA                                                                                                                                                          |
| • at 690 V                                                                                | 5 kA                                                                                                                                                           |
| short-circuit current making capacity (Icm)                                               |                                                                                                                                                                |
| • at 240 V                                                                                | 121 kA                                                                                                                                                         |
| • at 415 V                                                                                | 75.6 kA                                                                                                                                                        |
| • at 440 V                                                                                | 75.6 kA                                                                                                                                                        |
| • at 500 V                                                                                | 52.5 kA                                                                                                                                                        |
| • at 690 V                                                                                | 11.9 kA                                                                                                                                                        |
| design of short-circuit protection                                                        | For switching power values in DC networks, see the 3VA molded case circuit breaker device manual; link to be found under Service & Support in the last chapter |
| <b>Adjustable parameters</b>                                                              |                                                                                                                                                                |
| product feature / for L-tripping / can be switched on/off                                 | No                                                                                                                                                             |
| adjustable response value setting current (Ir) / of the L-trip / with I2t characteristic  |                                                                                                                                                                |
| • minimum                                                                                 | 441 A                                                                                                                                                          |
| • maximum                                                                                 | 630 A                                                                                                                                                          |
| adjustable response value delay time (tr) / for L-tripping / with I2t characteristic      |                                                                                                                                                                |
| • minimum                                                                                 | 1 s                                                                                                                                                            |
| • maximum                                                                                 | 1 s                                                                                                                                                            |
| adjustable response value setting current (Ii) / for I-tripping                           |                                                                                                                                                                |
| • minimum                                                                                 | 2 520 A                                                                                                                                                        |
| • maximum                                                                                 | 5 040 A                                                                                                                                                        |
| adjustable setting current (InN) / for N-tripping                                         |                                                                                                                                                                |
| • minimum                                                                                 | 0 A                                                                                                                                                            |
| • maximum                                                                                 | 0 A                                                                                                                                                            |
| product function / grounding protection                                                   | No                                                                                                                                                             |
| <b>Mechanical Design</b>                                                                  |                                                                                                                                                                |
| product component                                                                         |                                                                                                                                                                |
| • undervoltage release                                                                    | No                                                                                                                                                             |
| • voltage trigger                                                                         | No                                                                                                                                                             |
| • trip indicator                                                                          | No                                                                                                                                                             |
| height [in]                                                                               | 9.76 in                                                                                                                                                        |
| height                                                                                    | 248 mm                                                                                                                                                         |
| width [in]                                                                                | 5.43 in                                                                                                                                                        |
| width                                                                                     | 138 mm                                                                                                                                                         |
| depth [in]                                                                                | 4.33 in                                                                                                                                                        |
| depth                                                                                     | 110 mm                                                                                                                                                         |
| <b>Connections</b>                                                                        |                                                                                                                                                                |
| arrangement of electrical connectors / for main current circuit                           | Front terminal                                                                                                                                                 |
| type of electrical connection / for main current circuit                                  | nut keeper kit on both ends                                                                                                                                    |
| type of connectable conductor cross-sections / for flat-bar terminal connection / minimum | 20 x 1 mm                                                                                                                                                      |
| type of connectable conductor cross-sections / for flat-bar terminal connection / maximum | 35 x 10 mm                                                                                                                                                     |
| design of the surface / of the connections / on the top of the switch (N, 1, 3, 5)        | Silver                                                                                                                                                         |
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6)     | Silver                                                                                                                                                         |
| <b>Auxiliary circuit</b>                                                                  |                                                                                                                                                                |
| number of CO contacts / for auxiliary contacts                                            | 0                                                                                                                                                              |
| <b>Accessories</b>                                                                        |                                                                                                                                                                |
| product extension / optional / motor drive                                                | Yes                                                                                                                                                            |
| <b>Environmental conditions</b>                                                           |                                                                                                                                                                |
| protection class IP / on the front                                                        | IP40                                                                                                                                                           |
| ambient temperature                                                                       |                                                                                                                                                                |
| • during operation / minimum                                                              | -25 °C                                                                                                                                                         |
| • during operation / maximum                                                              | 70 °C                                                                                                                                                          |

- during storage / minimum
- during storage / maximum

-40 °C

80 °C

reference code / according to IEC 81346-2

Q

## Approvals / Certificates

### General Product Approval



EG-Konf.



[Confirmation](#)



CCC



VDE

[Miscellaneous](#)

### General Product Approval

#### EMV

#### Test Certificates

#### Marine / Shipping



RCM

[Miscellaneous](#)

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



BUREAU  
VERITAS

### Marine / Shipping

#### other

#### Environment



DNV



RMRS

[Confirmation](#)

[Miscellaneous](#)

[Miscellaneous](#)



EPD

### Environment

[Environmental Conformations](#)

[Environmental Conformations](#)

## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA1463-4EF32-0AA0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA1463-4EF32-0AA0>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA1463-4EF32-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA1463-4EF32-0AA0)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>



Subject to change without notice  
© Copyright Siemens



