

Motor-protective circuit-breaker, 660 V 690 V: 3 kW, Ir= 2.5 - 4 A, IP20



Powering Business Worldwide™

Part no. PKZM01-4
Catalog No. 278482
Alternate Catalog No. XTPB004BC1
EL-Nummer (Norway) 4365017

Delivery program

Product range	PKZM01 motor protective circuit-breakers up to 25 A with pushbutton actuation		
Basic function	Motor protection		
Notes	Also suitable for motors with efficiency class IE3.		
Connection technique	Screw terminals		
Max. motor rating			
AC-3			
220 V 230 V 240 V	P	kW	0.75
380 V 400 V 415 V	P	kW	1.5
440 V	P	kW	1.5
500 V	P	kW	2.2
660 V 690 V	P	kW	3
Rated uninterrupted current	I _u	A	4
Setting range			
Overload releases	I _r	A	2.5 - 4
			
short-circuit release	I _{rm}	A	62
			
max.	I _{rm}	A	62
Phase-failure sensitivity	IEC/EN 60947-4-1, VDE 0660 Part 102		
Notes	Overload trigger: tripping class 10 A Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.		

Technical data

General					
Standards			IEC/EN 60947, VDE 0660, UL, CSA		
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30		
Ambient temperature					
Storage	°C	- 40 - 80			
Open	°C	- 25 - +55			
Enclosed	°C	- 25 - 40			
Direction of incoming supply			as required		
Degree of protection					
Device	IP20				
Terminations	IP00				
Protection against direct contact when actuated from front (EN 50274)	Finger and back-of-hand proof				
Mechanical shock resistance half-sinusoidal shock 10 ms to IEC 60068-2-27	g	25			
Altitude	m	Max. 2000			
Terminal capacity main cable					
Screw terminals					
Solid	mm ²	1 x (1 - 6) 2 x (1 - 6)			
Flexible with ferrule to DIN 46228	mm ²	1 x (1 - 6) 2 x (1 - 6)			
Solid or stranded	AWG	18 - 10			

Stripping length	mm	10
Specified tightening torque for terminal screws	Nm	1.7
Main cable		
Main conducting paths		
Rated impulse withstand voltage	U_{imp}	V AC 6000
Overshoot category/pollution degree		III/3
Rated operational voltage	U_e	V AC 690
Rated uninterrupted current = rated operational current	$I_u = I_e$	A 4
Rated frequency	f	Hz 50/60
Current heat loss (3 pole at operating temperature)		W 5.33
Impedance per pole		mΩ 110
Lifespan, mechanical	Operations	$\times 10^6$ 0.05
Lifespan, electrical (AC-3 at 400 V)		
Lifespan, electrical	Operations	$\times 10^6$ 0.05
Max. operating frequency		Ops/h 25
Short-circuit rating		
DC		
Short-circuit rating		kA 60
Notes		up to 250 V
Motor switching capacity		
AC-3 (up to 690V)		A 4
DC-5 (up to 250V)		A 4 (3 contacts in series)

Trip blocks

Temperature compensation		
to IEC/EN 60947, VDE 0660	°C	- 5 ... 40
Operating range	°C	- 25 ... 55
Temperature compensation residual error for $T > 40$ °C		≤ 0.25 %/K
Setting range of overload releases	$\times I_u$	0.6 - 1
short-circuit release		Basic device, fixed: $15.5 \times I_u$
Short-circuit release tolerance		± 20%
Phase-failure sensitivity		IEC/EN 60947-4-1, VDE 0660 Part 102

Rating data for approved types

Switching capacity		
Maximum motor rating		
Three-phase		
200 V 208 V	HP	0.75
230 V 240 V	HP	0.75
460 V 480 V	HP	2
575 V 600 V	HP	3
Single-phase		
115 V 120 V	HP	0.125
230 V 240 V	HP	0.33
Short Circuit Current Rating, group protection	SCCR	
600 V High Fault		
SCCR (fuse)	kA	50
max. Fuse	A	600
SCCR (CB)	kA	50
max. CB	A	600

Design verification as per IEC/EN 61439

Technical data for design verification		
Rated operational current for specified heat dissipation	I_n	A 4

Heat dissipation per pole, current-dependent	P _{vid}	W	1.78
Equipment heat dissipation, current-dependent	P _{vid}	W	5.33
Static heat dissipation, non-current-dependent	P _{vs}	W	0
Heat dissipation capacity	P _{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Motor protection circuit-breaker (EC000074)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Motor protection circuit-breaker (ecl@ss10.0.1-27-37-04-01 [AGZ529016])			
Overload release current setting	A	2.5 - 4	
Adjustment range undelayed short-circuit release	A	62 - 62	
With thermal protection		No	
Phase failure sensitive		Yes	
Switch off technique		Thermomagnetic	
Rated operating voltage	V	690 - 690	
Rated permanent current I _u	A	4	
Rated operation power at AC-3, 230 V	kW	0.75	
Rated operation power at AC-3, 400 V	kW	1.5	
Type of electrical connection of main circuit		Screw connection	
Type of control element		Push button	
Device construction		Built-in device fixed built-in technique	
With integrated auxiliary switch		No	
With integrated under voltage release		No	
Number of poles		3	
Rated short-circuit breaking capacity I _{cu} at 400 V, AC	kA	50	
Degree of protection (IP)		IP20	

Height	mm	90
Width	mm	45
Depth	mm	93