

NH fuse-switch 3p box terminal 35 - 150 mm²; mounting plate; XNH1

Part no. XNH1-A250-BT
183044
EL Number (Norway) 1624019



Powering Business Worldwide™

General specifications

Product name	Eaton xEffect XNH device for mounting plate
Part no.	XNH1-A250-BT
EAN	4015081779710
Product Length/Depth	306 millimetre
Product height	117 millimetre
Product width	184 millimetre
Product weight	2.031 kilogram
Compliances	RoHS conform
Certifications	IEC/EN 60947-3
Product Tradename	xEffect
Product Type	XNH device for mounting plate
Product Sub Type	None

Delivery program

Type	Basic device
Color	Gray
Number of poles	Three-pole
Actuator type	Cover grip

Technical Data - Electrical

Voltage test	Yes, sliding inspection windows
Voltage rating at AC	400 V (AC-23B) 500 V (AC-22B) 690 V (AC-21B)
Voltage rating at DC	250 V (DC-22B) 440 V (DC-21B)
Rated operating voltage (Ue) at AC - max	690 V
Rated insulation voltage (Ui)	800 V AC
Rated impulse withstand voltage (Uimp)	8 kV
Rated uninterrupted current (Iu)	250 A
Rated conditional short-circuit current (Iq)	120 kA
Rated operation current (Ie)	250 A
Rated operational current	250 A (AC-22B) 250 A (AC-21B) 250 A (DC-21B) 250 A (DC-22B) 250 A (AC-23B)
Rated short-time withstand current (Icw)	6 kA
Rated conditional short-circuit rating	100 kA (690 V) 120 kA (500 V)
Conditioned rated short-circuit current Iq	120 kA
Frequency rating	40 Hz - 60 Hz
Frequency rating of contacts	40 Hz - 60 Hz
Creepage resistance	CTI 600
Power rating at AC-23, 400 V	0 kW
Rated operation power at AC-23, 400 V	0 kW
Permitted power loss per fuse link - max	23 W
Electrical connection type of main circuit	Frame clamp
Operating altitude without derating - max	2000 mm
Overvoltage category	III
Pollution degree	3
Direction of incoming supply	As required

Technical Data - Mechanical

	200 operations
Activation type	Dependent manual activation
Actuator position	Front side
Size	NH1 fuse
Mounting method	DIN rail Mounting plate
Mounting position	Vertical or horizontal
Material	Polyamide
Degree of protection	IP10 (handle cover open, XNH installed) IP20 (operating status, XNH installed) IP2XC (contact protection, XNH installed)
Degree of protection (front side)	Other
Connection type	Box terminal
Terminal capacity (copper band)	6 mm x 16 mm x 0.8 mm (6x) at box terminal
Terminal capacity (copper busbar)	30 mm x 10 mm Max. 37 mm cable lug width at flange connection Bolt diameter at flange connection: M10
Terminal capacity (copper strip)	16 mm x 0.8 mm (10x) at box terminal
Terminal capacity (stranded cable)	25 mm ² - 150 mm ² at box terminal 10 mm ² - 150 mm ² at clamp-type terminal 35 mm ² - 150 mm ² at box terminal 70 mm ² - 95 mm ² (2x) at double clamp-type terminal
Cable entry type	Other
Locking facility	Yes, optional
Suitable for fuses	NH1
Lifespan, mechanical	1400 operations
Design verification as per IEC/EN 61439 - technical data	
Rated operational current for specified heat dissipation (In)	250 A
Equipment heat dissipation, current-dependent	16 W
Heat dissipation per pole, current-dependent	5.3 W
Heat dissipation at 80% without fuses	10.2 W
Ambient operating temperature details	Ambient temperature range: -25 °C - 55 °C
Heat deflection temperature	125 °C
Design verification as per IEC/EN 61439	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Is the panel builder's responsibility.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Ui = 800 V AC
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Additional information

Features		Halogen free Standard sealable
Flammability characteristics (UL)		Self-extinguishing (UL 94)
Special features		Current paths of electrolytic copper, silver-plated Permanent operation (rated operating mode)
Suitable for		Ground mounting

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Fuse switch disconnector (EC001040)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector (ecl@ss13-27-37-14-01 [AKF058018])

Version as main switch		No
Version as safety switch		No
Max. rated operation voltage Ue AC	V	690
Rated permanent current Iu	A	250
Rated operation power at AC-23, 400 V	kW	0
Conditioned rated short-circuit current Iq	kA	120
Rated short-time withstand current Icw	kA	6
Suitable for fuses		NH1
Number of poles		3
With error protection		No
Type of electrical connection of main circuit		Frame clamp
Cable entry		Other
Equipped with connectors		No
Suitable for floor mounting		Yes
Suitable for front mounting		No
Suitable for busbar mounting		No
Type of control element		Cover grip
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		Other