

## Restarting device-set, 220-240VAC, 6HP

**Part no.** Z-FW-LP/M0  
**Catalog No.** 290171  
**Alternate Catalog No.** Z-FW-LP/M0



Powering Business Worldwide™

## Delivery program

Basic function		Accessories for miniature circuit-breaker Accessories for residual current circuit-breakers
Basic function accessories		Restarting device
Application		Switchgear for industrial and advanced commercial applications
Product range		Accessory
Side mounting		for fitting on right to: CLS6, PFIM, PFHM-4p, dRCM, Z-A40, PFR, Z-MS

## Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I <sub>n</sub>	A	0
Heat dissipation per pole, current-dependent	P <sub>vid</sub>	W	0
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	0
Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	3.5
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	40
			0

## Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])		
Device fitting		Universal
Additional equipment		Monitoring unit with automatic reclosing
Installed at the factory		No
Width in number of modular spacings		6
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	0
Rated voltage	V	230
Voltage type for actuating		AC
With auto test for earth leakage function		Yes
Suitable for max. number of poles main contact unit (total)		0
Suitable for max. current main contact unit	A	0