

Restarting device-set, 24-48VDC, 6HP



Part no. Z-FW-LPD/MO
Catalog No. 290172
Alternate Catalog No. Z-FW-LPD/MO

Similar to illustration

Delivery program

| | | |
|----------------------------|--|--|
| Basic function | | Accessories for miniature circuit-breaker Accessories for residual current circuit-breakers |
| Basic function accessories | | Restarting device |
| Application | | Switchgear for industrial and advanced commercial applications |
| Product range | | Accessory |
| Side mounting | | for fitting on right to: CLS6, PFIM, PFHM-4p, dRCM, Z-A40, PFR, Z-MS |

Design verification as per IEC/EN 61439

| Technical data for design verification | | | |
|--|-------------------|----|-----|
| Rated operational current for specified heat dissipation | I _n | A | 0 |
| Heat dissipation per pole, current-dependent | P _{vid} | W | 0 |
| Equipment heat dissipation, current-dependent | P _{vid} | W | 0 |
| Static heat dissipation, non-current-dependent | P _{vs} | W | 0.8 |
| Heat dissipation capacity | P _{diss} | W | 0 |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 40 |
| | | | 0 |

Technical data ETIM 8.0

| | | |
|---|---|--|
| Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013]) | | |
| Device fitting | | Universal |
| Additional equipment | | Monitoring unit with automatic reclosing |
| Installed at the factory | | No |
| Width in number of modular spacings | | 6 |
| Number of contacts as normally open contact | | 0 |
| Number of contacts as normally closed contact | | 0 |
| Number of contacts as change-over contact | | 0 |
| Number of fault-signal switches | | 0 |
| Rated switch current | A | 0 |
| Rated voltage | V | 48 |
| Voltage type for actuating | | DC |
| With auto test for earth leakage function | | Yes |
| Suitable for max. number of poles main contact unit (total) | | 0 |
| Suitable for max. current main contact unit | A | 0 |