

Remote tripping module, for PKNM, PKDM, PFHM-2p

Part no. Z-KAM
Catalog No. 248294
Alternate Catalog No. Z-KAM

Delivery program

Basic function			Accessories for combined residual-current/power circuit-breakers
Basic function accessories			Residual-current release module
Application			Switchgear for industrial and advanced commercial applications
Product range			Accessory
Side mounting			for fitting on left to: FI/LS

Technical data

Electrical

Contact function			1 NO
Rated operational voltage	U _e	V AC	230(400)
Rated frequency	f	Hz	50/60

Mechanical

Mounting width		mm	8.8 (0.5 SU)
Degree of protection			
Integrated			IP40

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecI@ss10.0.1-27-14-35-02 [AKE327013])			
Device fitting			Other
Additional equipment			Remote release
Installed at the factory			No
Width in number of modular spacings			0.5
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	0
Rated voltage		V	400
Voltage type for actuating			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			0
Suitable for max. current main contact unit		A	0