

## Two way switchp22 CO, 16A, 230 V, 20kA

Part no. **Z-S/2WTN**  
 Catalog No. **248348**



Similar to illustration

## Design verification as per IEC/EN 61439

Technical data for design verification		
Rated operational current for specified heat dissipation	I <sub>n</sub>	A 20

## Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)		
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss10.0.1-27-14-23-01 [AFZ813014])		
Switching function		Two-way switch
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		2
Number of poles		2
Rated current	A	20
Rated voltage	V	240
Min. rated voltage	V	0
Rated switching capacity	kA	0.025
Short-circuit breaking capacity (Icw)	kA	10
Voltage type		AC
With signal lamp		No
Colour calotte		Other
Lamp type		Other
Lamp socket		Other
Max. lamp power	W	0
Width in number of modular spacings		2
Built-in depth	mm	80
Degree of protection (IP)		IP40
Imprint/indication		EV000154