

Undervoltage release, 400 V, non-delayed, 1HP

Part no. Z-USA/400
Catalog No. 248290
Alternate Catalog No. Z-USA/400



Similar to illustration

Delivery program

Basic function		Accessories for miniature circuit-breaker
Basic function accessories		Undervoltage release
Application		Switchgear for industrial and advanced commercial applications
Tripping	s...	non-delayed
Product range		Accessory
Side mounting		for fitting on left to: FAZ

Technical data

Electrical

Rated operational voltage	U _e	V AC	400
Tripping threshold	x U _n		0.5
Rated frequency	f	Hz	50/60

Mechanical

Mounting width	mm	17.5 (1 MU)
Degree of protection		
Integrated		IP40
Terminals		Open Mouth/Lift

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	°C	-5	
Operating ambient temperature max.	°C	40	

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])			
Device fitting		Universal	
Additional equipment		Under voltage coil	
Installed at the factory		No	
Width in number of modular spacings		1	
Number of contacts as normally open contact		1	
Number of contacts as normally closed contact		1	
Number of contacts as change-over contact		0	
Number of fault-signal switches		0	
Rated switch current	A	0	
Rated voltage	V	400	
Voltage type for actuating		AC	
With auto test for earth leakage function		No	
Suitable for max. number of poles main contact unit (total)		1	
Suitable for max. current main contact unit	A	0	